



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
02.01.2003 Bulletin 2003/01

(51) Int Cl.7: **H04R 7/04, H04M 1/03**

(21) Application number: **02013996.0**

(22) Date of filing: **26.06.2002**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
 Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **28.06.2001 JP 2001196033**
19.07.2001 JP 2001219370
02.10.2001 JP 2001306145

(71) Applicant: **MATSUSHITA ELECTRIC INDUSTRIAL**
CO., LTD.
Kadoma-shi, Osaka 571-8501 (JP)

(72) Inventors:
 • **Saiki, Shuji**
Uda-gun, Nara 633-0206 (JP)
 • **Usuki, Sawako**
Kobe-shi, Hyogo 654-0152 (JP)
 • **Konishi, Shuhei**
Yao-shi, Osaka 581-0018 (JP)


(74) Representative: **Schwabe - Sandmair - Marx**
Stuntzstrasse 16
81677 München (DE)

(54) **Speaker system, mobile terminal device, and electronic device**

(57) A speaker system includes a display panel for displaying an image; a transparent panel provided such that the image displayed in the display panel is viewed through the transparent panel; an electric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and an acoustic signal transfer mem-

ber for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the display panel and the transparent panel. The transparent panel is allowed to be vibrated by the sound transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member.

FIG. 1B



Description

BACKGROUND OF THE INVENTION

1. FIELD OF THE INVENTION:

[0001] The present invention relates to a speaker system, and a mobile terminal device and an electronic device including the speaker system.

2. DESCRIPTION OF THE RELATED ART:

[0002] With reference to Figure 27, a conventional cellular telephone 15 will be described. Japanese Laid-Open Publication No. 8-275293 discloses a speaker system for vibrating a housing of a cellular phone by a driver directly attached to the housing so as to output a vibration or sound.

[0003] The cellular phone 15 includes a housing 10, an antenna 11, a sound board 12 which is thinner in a rear peripheral portion than the rest thereof, a driver 13 provided on a rear surface of the sound board 12, and a character display panel 14 provided on a front surface of the housing 10 adjacent to the sound board 12.

[0004] An operation of the cellular phone 15 will be described. When an electric signal is applied to the driver 13, the vibration of the driver 13 is directly transferred to the sound board 12 provided in the housing 10. Then, the sound board 12 is vibrated so as to generate a sound. The sound board 12 is thinner in the rear peripheral portion than the rest thereof, so as to be easily vibrated.

[0005] The cellular phone 15 having such a structure has the following problem. Due to the sound board 12, the planar size of the character display panel 14 for displaying a phone number or the like is inevitably provided in a small, limited space below the sound board 12. Accordingly, it is conventionally difficult to enlarge the display panel 14 for more conveniently displaying, for example, characters of e-mails or images received through the Internet.

[0006] A conventional electronic device or a mobile terminal device including the above-described speaker system has the following problem. In these devices, a display panel and a speaker are located separately. Therefore, the position where the image is displayed is different from the position from which the sound is output. This gives the user a sense of unnaturalness. For example, when the electronic device or the mobile terminal device is used as a video telephone, the user has a sense of unnaturalness since the position of the image representing the person on the other end is different from the position from which his/her voice is output. It is more natural and desirable that the position where the image is displayed to the user is the same as the position from which the sound is output to the user.

SUMMARY OF THE INVENTION

[0007] According to one aspect of the invention, a speaker system includes a display panel for displaying an image; a transparent panel provided such that the image displayed in the display panel is viewed through the transparent panel; an electric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the display panel and the transparent panel. The transparent panel is allowed to be vibrated by the sound transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member.

[0008] In one embodiment of the invention, the acoustic signal transfer member is a housing for supporting the transparent panel. The housing has a sound hole. The sound is transferred to the space via the sound hole.

[0009] In one embodiment of the invention, the speaker system further includes an elastic member for supporting a peripheral portion of the transparent panel.

[0010] In one embodiment of the invention, the acoustic signal transfer member is an acoustic pipe.

[0011] In one embodiment of the invention, a thickness of a peripheral portion of the transparent panel is smaller than a thickness of a central portion of the transparent panel.

[0012] In one embodiment of the invention, the transparent panel is a film.

[0013] In one embodiment of the invention, the electric-mechanical-acoustic-transducer includes a mechanical vibration section for generating a mechanical vibration.

[0014] In one embodiment of the invention, the speaker system includes at least one more electric-mechanical-acoustic-transducer; and at least one more acoustic signal transfer member. The electric-mechanical-acoustic-transducers each include a diaphragm and each output a sound by vibrating the diaphragm in accordance with an electric signal. The acoustic signal transfer members each transfer the sound output from the respective electric-mechanical-acoustic-transducer to the space. The acoustic signal transfer members are connected to the space at different positions.

[0015] In one embodiment of the invention, the acoustic signal transfer member has a sound hole for transferring the sound. The sound hole extends in a direction parallel to a direction in which the display panel extends.

[0016] In one embodiment of the invention, the electric-mechanical-acoustic-transducer includes a housing for surrounding the diaphragm. The housing has an opening extending in a direction vertical to a direction in which the diaphragm vibrates. The opening is in connection with the acoustic signal transfer member.

[0017] According to another aspect of the invention,

a mobile terminal device includes a speaker system; and a housing for supporting the speaker system. The speaker system includes a display panel for displaying an image; a transparent panel provided such that the image displayed in the display panel is viewed through the transparent panel; an electric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the display panel and the transparent panel, wherein the transparent panel is allowed to be vibrated by the sound transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member. The mobile terminal device further includes an antenna for receiving a wireless signal; and a signal output section for outputting an electric signal to the electric-mechanical-acoustic-transducer based on the wireless signal received by the antenna. The electric signal represents at least one of a received sound, a call arrival sound, music and voice.

[0018] In one embodiment of the invention, when the electric signal represents the received sound, the transparent panel acts as a receiver.

[0019] In one embodiment of the invention, when the electric signal represents one of the call arrival sound, the music and the voice, the transparent panel acts as a loudspeaker.

[0020] In one embodiment of the invention, the electric-mechanical-acoustic-transducer includes one more diaphragm. The housing has a sound hole. One of the diaphragms is provided so as to face the acoustic signal transfer member, and the other diaphragm is provided so as to face the sound hole.

[0021] According to still another aspect of the invention, an electronic device includes a speaker system; and a housing for supporting the speaker system. The speaker system includes a display panel for displaying an image; a transparent panel provided such that the image displayed in the display panel is viewed through the transparent panel; an electric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the display panel and the transparent panel, wherein the transparent panel is allowed to be vibrated by the sound transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member.

[0022] In one embodiment of the invention, the electronic device further includes a control section for controlling an operation of the electronic device. The transparent panel also acts as a touch panel for detecting a contact of a contact member with a position of the transparent panel corresponding to an operation menu icon

displayed in the display panel. The control section causes the electronic device to operate in accordance with the operation menu icon corresponding to the position of the transparent panel which is in contact with the contact member.

[0023] In one embodiment of the invention, the touch panel is one of an electrostatic system touch panel, an optical system touch panel, an electromagnetic system touch panel, and an ultrasonic system touch panel.

[0024] According to still another aspect of the invention, a speaker system includes a display panel for displaying an image; a transparent panel provided such that the image displayed in the display panel is viewed through the transparent panel; a substrate provided between the display panel and the transparent panel such that the image is viewed through the substrate; an electric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the transparent panel and the substrate. The transparent panel is allowed to be vibrated by the sound transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member.

[0025] In one embodiment of the invention, the substrate has a sound hole. The substrate acts as the acoustic signal transfer member.

[0026] In one embodiment of the invention, the space is provided among a spacer, for connecting a peripheral portion of the transparent panel and a peripheral portion of the substrate, the transparent panel and the substrate.

[0027] In one embodiment of the invention, the transparent panel is a film.

[0028] In one embodiment of the invention, the acoustic signal transfer member is an acoustic pipe.

[0029] In one embodiment of the invention, the speaker system includes at least one more electric-mechanical-acoustic-transducer; and at least one more acoustic signal transfer member. The electric-mechanical-acoustic-transducers each include a diaphragm and each output a sound by vibrating the diaphragm in accordance with an electric signal. The acoustic signal transfer members each transfer the sound output from the respective electric-mechanical-acoustic-transducer to the space. The acoustic signal transfer members are connected to the space at different positions.

[0030] According to still another aspect of the invention, a mobile terminal device includes a speaker system; and a housing for supporting the speaker system. The speaker system includes a display panel for displaying an image; a transparent panel provided such that the image displayed in the display panel is viewed through the transparent panel; a substrate provided between the display panel and the transparent panel such that the image is viewed through the substrate; an elec-

tric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the transparent panel and the substrate, wherein the transparent panel is allowed to be vibrated by the sound transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member. The mobile terminal device further includes an antenna for receiving a wireless signal; and a signal output section for outputting an electric signal to the electric-mechanical-acoustic-transducer based on the wireless signal received by the antenna. The electric signal represents at least one of a received sound, a call arrival sound, music and voice.

[0031] In one embodiment of the invention, when the electric signal represents the received sound, the transparent panel acts as a receiver.

[0032] In one embodiment of the invention, when the electric signal represents one of the call arrival sound, the music and the voice, the transparent panel acts as a loudspeaker.

[0033] In one embodiment of the invention, the electric-mechanical-acoustic-transducer has one more diaphragm. The housing has a sound hole. One of the diaphragms is provided so as to face the acoustic signal transfer member, and the other diaphragm is provided so as to face the sound hole.

[0034] According to still another aspect of the invention, an electronic device includes a speaker system; and a housing for supporting the speaker system. The speaker system includes a display panel for displaying an image; a transparent panel provided such that the image displayed in the display panel is viewed through the transparent panel; a substrate provided between the display panel and the transparent panel such that the image is viewed through the substrate; an electric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the transparent panel and the substrate, wherein the transparent panel is allowed to be vibrated by the sound transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member.

[0035] In one embodiment of the invention, the electronic device further includes a control section for controlling an operation of the electronic device. The transparent panel also acts as a touch panel for detecting a contact of a contact member with a position of the transparent panel corresponding to an operation menu icon displayed in the display panel. The control section causes the electronic device to operate in accordance with the operation menu icon corresponding to the position

of the transparent panel which is in contact with the contact member.

[0036] In one embodiment of the invention; the electronic device further includes a first transparent electrode having an electric resistance and provided on a surface of the transparent panel facing the substrate; and a second transparent electrode having an electric resistance and provided on a surface of the substrate facing the transparent panel.

[0037] According to still another aspect of the invention, an electronic device includes a speaker system; and a housing for supporting the speaker system. The speaker system includes a panel; an electric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the panel and the housing. The panel is allowed to be vibrated by the sound transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member. The electronic device further includes a control section for controlling an operation of the electronic device. The panel also acts as a touch panel for detecting a contact of a contact member with a position of the panel corresponding to an operation menu provided on the panel. The control section causes the electronic device to operate in accordance with an item of the operation menu corresponding to the position of the panel which is in contact with the contact member.

[0038] According to still another aspect of the invention, an electronic device includes a speaker system; and a housing for supporting the speaker system. The speaker system includes a panel; a substrate provided so as to face the panel; an electric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the panel and the substrate. The panel is allowed to be vibrated by the sound transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member. The electronic device further includes a control section for controlling an operation of the electronic device. The panel also acts as a touch panel for detecting a contact of a contact member with a position of the panel corresponding to an item of an operation menu provided on the panel. The control section causes the electronic device to operate in accordance with the item of the operation menu corresponding to the position of the panel which is in contact with the contact member.

[0039] In one embodiment of the invention, the electric signal represents at least one of a received sound, a call arrival sound, and audio information for a plurality of channels. When the electric signal represents at least

one of the received sound and the call arrival sound, the electric signal is input to the electric-mechanical-acoustic-transducers. When the electric signal represents the audio information for the plurality of channels, an electric signal representing audio information for each of the plurality of channels is input to the respective electric-mechanical-acoustic-transducer.

[0040] In one embodiment of the invention, the speaker system includes at least one more electric-mechanical-acoustic-transducer, and at least one more acoustic signal transfer member, and the electric-mechanical-acoustic-transducers each include a diaphragm and each output a sound by vibrating the diaphragm in accordance with an electric signal. The acoustic signal transfer members each transfer the sound output from the respective electric-mechanical-acoustic-transducer to the space. The acoustic signal transfer members are connected to the space at different positions. When the electric signal represents at least one of the received sound and the call arrival sound, the electric signal is input to the electric-mechanical-acoustic-transducers. When the electric signal represents the audio information for the plurality of channels, an electric signal representing audio information for each of the plurality of channels is input to the respective electric-mechanical-acoustic-transducer.

[0041] In one embodiment of the invention, the electric signal represents at least one of a received sound, a call arrival sound, and audio information for a plurality of channels. When the electric signal represents at least one of the received sound and the call arrival sound, the electric signal is input to the electric-mechanical-acoustic-transducers. When the electric signal represents the audio information for the plurality of channels, an electric signal representing audio information for each of the plurality of channels is input to a respective one of the electric-mechanical-acoustic-transducers.

[0042] Thus, the invention described herein makes possible the advantages of providing (1) a speaker system in which the position where an image is displayed to the user is the same as the position from which a sound is output to the user; and (2) a speaker system providing a higher level of freedom of location in an electronic device or a mobile terminal device.

[0043] These and other advantages of the present invention will become apparent to those skilled in the art upon reading and understanding the following detailed description with reference to the accompanying figures.

BRIEF DESCRIPTION OF THE DRAWINGS

[0044]

Figure 1A is a plan view of a speaker system according to a first example of the present invention;

Figure 1B is a cross-sectional view of the speaker system taken along chain line A-B shown in Figure

1A;

Figure 2 is a cross-sectional view of an electric-mechanical-acoustic-transducer included in the speaker system according to the first example;

Figure 3 is a graph illustrating a sound pressure vs. frequency characteristic of the speaker system according to the first example;

Figure 4 is a plan view of a speaker system according to a second example of the present invention;

Figure 5 is a cross-sectional view of the speaker system taken along chain line C-D shown in Figure 4;

Figure 6 is a graph illustrating a sound pressure vs. frequency characteristic of the speaker system according to the second example;

Figure 7A is a plan view of a speaker system according to a third example of the present invention;

Figure 7B is a cross-sectional view of the speaker system taken along chain line E-F shown in Figure 7A;

Figure 8 is a cross-sectional view of an electric-mechanical-acoustic-transducer included in the speaker system according to the third example;

Figure 9A is a plan view of another speaker system according to the third example of the present invention;

Figure 9B is a cross-sectional view of the speaker system taken along chain line G-H shown in Figure 9A;

Figure 10A is a plan view of a speaker system according to a fourth example of the present invention;

Figure 10B is a cross-sectional view of the speaker system taken along chain line I-J shown in Figure 10A;

Figure 11 is a cross-sectional view of an electric-mechanical-acoustic-transducer included in the speaker system according to the fourth example;

Figure 12 is a cross-sectional view of another speaker system according to the fourth example of the present invention;

Figure 13 is a partially cut plan view of a mobile terminal device according to a fifth example of the present invention;

Figure **14** is a block diagram illustrating an internal structure of the mobile terminal device in the fifth example;

Figure **15** is a partially cut plan view of a mobile terminal device according to a sixth example of the present invention;

Figure **16** is a block diagram illustrating an internal structure of the mobile terminal device in the sixth example;

Figure **17** is a partially cut plan view of a mobile terminal device according to a seventh example of the present invention;

Figure **18** is a block diagram illustrating an internal structure of the mobile terminal device in the seventh example;

Figure **19A** is a partially cut plan view of a mobile terminal device according to an eighth example of the present invention;

Figure **19B** is a partially cut side view of the mobile terminal device according to the eighth example;

Figure **19C** is a bottom view of the mobile terminal device according to the eighth example;

Figure **20** is a cross-sectional view of an electric-mechanical-acoustic-transducer included in the mobile terminal device according to the eighth example;

Figure **21A** is a plan view of an electronic device according to a ninth example of the present invention;

Figure **21B** is across-sectional view of the electronic device taken along chain line K-L shown in Figure **21A**;

Figure **22A** is a plan view of an electronic device according to a tenth example of the present invention;

Figure **22B** is a cross-sectional view of the electronic device taken along chain line M-N shown in Figure **22A**;

Figure **23A** is a plan view of an electronic device according to an eleventh example of the present invention;

Figure **23B** is a cross-sectional view of the electronic device taken along chain line K₁-L₁ shown in Figure **23A**;

Figure **24A** is a plan view of another electronic device according to the eleventh example of the present invention;

Figure **24B** is across-sectional view of the electronic device taken along chain line K₂-L₂ shown in Figure **24A**;

Figure **25** is an isometric view of an electronic device according to a twelfth example of the present invention;

Figure **26** is a cross-sectional view of a speaker system included in the electronic device taken along chain line O-P shown in Figure **25**; and

Figure **27** is a plan view of a conventional speaker system.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0045] Hereinafter, the present invention will be described by way of illustrative examples with reference to the accompanying drawings.

(Example 1)

[0046] A speaker system **1000** according to a first example of the present invention will be described with reference to Figures **1A** and **1B**. Figure **1A** is a plan view of the speaker system **1000**, and Figure **1B** is a cross-sectional view of the speaker system **1000** taken along chain line **A-B** shown in Figure **1A**.

[0047] The speaker system **1000** includes a display panel **21** for displaying an image, a transparent panel **24** located so as to allow an image displayed in the display panel **21** to be viewed through the transparent panel **24**, an electric-mechanical-acoustic-transducer **22** having a diaphragm **45** (Figure **2**) for vibrating the diaphragm **45** in accordance with an electric signal so as to output a sound, an elastic member **25** connected to a peripheral portion of the transparent panel **24**, and a housing **20** for supporting the transparent panel **24** and the display panel **21**.

[0048] The speaker system **1000** has a space **26** between the display panel **21** and the transparent panel **24**. The space **26** is preferably a closed space. The housing **20** has a sound hole **23**. The housing **20** acts as an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer **22** to the space **26**. The peripheral portion of the transparent panel **24** is supported by the elastic member **26**, and thus the transparent panel **24** can be vibrated by the sound transferred from the electric-mechanical-acoustic-transducer **22** to the space **26** via the sound hole **23**. The housing **20** supports the transparent panel **24** via the elastic member **25**. The transparent

panel 24 has an area which is larger than the area of the diaphragm 45. The display panel 21 is, for example, a liquid crystal display. The transparent panel 24 is formed of glass, an acrylic resin or other materials transmissive with respect to visible light.

[0049] Figure 2 is a cross-sectional view of the electric-mechanical-acoustic-transducer 22. In this example, the electric-mechanical-acoustic-transducer 22 is a dynamic speaker.

[0050] The electric-mechanical-acoustic-transducer 22 includes a cup-shaped yoke 40, a magnet 41 provided on a central part of the yoke 40, a plate 42 provided on a top surface of the magnet 41, a voice coil 44 inserted into a magnetic gap 43 between the yoke 40 and the plate 42, the diaphragm 45 connected to the voice coil 44, and a housing 46 for supporting a peripheral portion of the diaphragm 45. The yoke 40 is provided on a central part of the housing 46. The housing 46 is connected to the housing 20 such that the diaphragm 45 and the sound hole 23 face each other.

[0051] An exemplary operation of the speaker system 1000 will be described.

[0052] When an electric signal is applied to the voice coil 44 inserted into the magnetic gap 43, a driving force is generated in the voice coil 44. Then, the diaphragm 45 connected to the voice coil 44 is vibrated. Thus, a sound is generated. The sound generated by the diaphragm 45 is transferred to the space 26 via the sound hole 23. The transparent panel 24 supported by the elastic member 25 in the peripheral portion thereof is vibrated by the pressure of the sound transferred to the space 26 and thus generates a sound.

[0053] Figure 3 is a graph illustrating measuring results of a sound pressure vs. frequency characteristic of the speaker system 1000. The measurement was performed as follows. As the electric-mechanical-acoustic-transducer 22, a dynamic speaker having a speaker diameter of 18 mm was used. As the transparent panel 24, a transparent acrylic resin plate having a length of 60 mm, a width of 35 mm and a thickness of 1.7 mm was used. A microphone was placed at a position 0.1 m away from the speaker system 1000. A power of 0.1 W was applied to the electric-mechanical-acoustic-transducer 22.

[0054] Characteristic curve I in Figure 3 represents a sound output only from the electric-mechanical-acoustic-transducer 22 in the absence of the transparent panel 24 (comparative example). Characteristic curve II represents a sound output from the transparent panel 24 (the present invention). The sound level of characteristic curve II is lower than that of a characteristic curve I in a high frequency range of 3 kHz or higher.

[0055] The reduction in the sound pressure can be alleviated by adjusting the acoustic capacitance of the space 26 or by adjusting the weight of the transparent panel 24. More specifically, the sound pressure level can be raised in the above-described high frequency range by decreasing the acoustic capacitance of the

space 26 by reducing the width of the space 26 between the display panel 21 and the transparent panel 24. The sound pressure level can be raised in the above-described high frequency range also by reducing the weight of the transparent panel 24. The high frequency characteristic of the speaker system 1000 can be controlled by forming the transparent panel 24 of a material having a relatively small specific gravity or, by adjusting the thickness of the transparent panel 24. The width of the space 26 and the weight of the transparent panel 24 are adjusted in accordance with the bandwidth of the frequency range of the sound to be reproduced.

[0056] In the dynamic speaker having the speaker diameter of 18 mm used as the electric-mechanical-acoustic-transducer 22, the diaphragm 45 was formed of an acrylic film having a thickness of 20 μ m and a weight of about 6 mg. The voice coil 44 was formed of a copper wire having a diameter of 0.055 mm and a weight of 25 mg. The diameter of the voice coil 44 was 8 mm.

[0057] The transparent panel 24 formed of an acrylic resin (length: 60 mm; width: 35 mm; thickness: 1.7 mm) weighed about 4200 mg. The ratio of the weight of the transparent panel 24 to the total weight of the diaphragm 45 and the voice coil 44 is $4200 \text{ mg} / (6 \text{ mg} + 25 \text{ mg}) =$ about 135. The weight of the transparent panel 24 is about 135 times the total weight of the diaphragm 45 and the voice coil 44. Therefore, in the case where the voice coil 44 is connected to the transparent panel 24 (comparative example), the transparent panel 24 cannot be substantially vibrated directly by the voice coil 44. As a result, substantially no sound is generated from the transparent panel 24.

[0058] In the speaker system 1000 in this example, the heavy transparent panel 24 can be sufficiently vibrated by a small force, by the following principle. When the voice coil 44 drives the diaphragm 45 and thus the diaphragm 45 applies a pressure to the space 26, the pressure applied to the space 26 is transferred to the transparent panel 24. Thus, the transparent panel 24 vibrates. Where S_1 is the effective vibration area of the diaphragm 45, S_2 is the vibration area of the transparent panel 24, and M_2 is the weight of the transparent panel 24, the equivalent weight of the transparent panel 24 with respect to the voice coil 44 is $M_2 / (S_2 / S_1)^2$, owing to the effect of the acoustic transformer.

[0059] In the above-described example, the effective vibration area of the diaphragm 45 (S_1) is 98.5 mm and the vibration area of the transparent panel 24 (S_2) is 2100 mm². (Assuming that the effective radius of vibration of the diaphragm 45 is from the center of the edge portion to a substantially central position of the diaphragm 45, the effective radius of vibration of the diaphragm 45 is 5.6 mm although the apparent diameter of the diaphragm 45 is 18 mm.) The equivalent weight of the transparent panel 24 with respect to the voice coil 44 is $4200 \text{ mg} / (2100 \text{ mm}^2 / 98.5 \text{ mm}^2)^2 = 9.2 \text{ mg}$. The sum of the total weight of the diaphragm 45 and the voice coil

44 and the equivalent weight of the transparent panel **24** is $6 \text{ mg} + 25 \text{ mg} + 9.2 \text{ mg} = 40.2 \text{ mg}$. Accordingly, the transparent panel **24** can be vibrated by a force which can vibrate an object having a weight of 40.2 mg (total weight of the diaphragm **45**, the voice coil **44** and the transparent panel **24**). The weight of the 40.2 mg is about 1.3 times the total weight of the diaphragm **45** and the voice coil **44** (31 mg). Therefore, the transparent panel **24** can be sufficiently vibrated by the force generated in the voice coil **44**.

[0060] In this manner, the electric-mechanical-acoustic-transducer **22** vibrates the transparent panel **24** via the space **26**. Thus, the speaker system **1000**, in which the transparent panel **24** having a large area and a great weight is vibrated by a small force as a diaphragm for reproducing an acoustic signal, can be realized.

[0061] The transparent panel **24** is transmissive with respect to visible light, and therefore can reproduce an acoustic signal without shielding the image displayed in the display panel **21**. The transparent panel **24** is located such that the image displayed in the display panel **21** can be viewed through the transparent panel **24**. Therefore, the position where the image is displayed to the user can be the same as the position from which a sound is output to the user. Owing to such a structure, the user does not have any sense of unnaturalness. The system **1000** having such a structure may be mounted on an electronic device or a mobile terminal device (e.g., a personal computer, a TV, a game machine, or a cellular phone) including an image or sound signal processing circuit.

[0062] The transparent panel **24** is supported by the elastic member **25**, and thus the entire surface of the transparent panel **24** is vibrated by the pressure of the sound generated by the electric-mechanical-acoustic-transducer **22**. Therefore, the acoustic characteristics such as, for example, the reproduction sound volume and the reproduction frequency band can be improved. Especially, the reproduction frequency band in a low frequency range can be expanded.

[0063] In the first example, the elastic member **25** for supporting the peripheral portion of the transparent panel **24** is provided on a bottom surface of the transparent panel **24**. Alternatively, the elastic member **25** may be provided so as to cover a side surface of the peripheral portion of the transparent panel **24**. The space **26**, surrounded by the transparent panel **24**, the display panel **21**, the elastic member **25**, the housing **20** and the electric-mechanical-acoustic-transducer **22**, preferably maintains a high level of airtightness in order to prevent the sound output from the diaphragm **45** from leaking outside.

[0064] In the first example, a dynamic speaker is used as the electric-mechanical-acoustic-transducer **22**. Alternatively, any type of speaker which outputs a sound from a diaphragm is usable, and substantially the same effect is provided. Exemplary speakers usable include an electromagnetic speaker, a piezoelectric speaker,

and a static speaker. The electric-mechanical-acoustic-transducer **22** may be round, elliptic or rectangular. When the electric-mechanical-acoustic-transducer **22** is elliptic or rectangular, the space in which the display panel **21** can be provided is enlarged, i.e., the planar size of the display panel **21** can be increased.

(Example 2)

[0065] A speaker system **1100** according to a second example of the present invention will be described with reference to Figures **4** and **5**. Figure **4** is a plan view of the speaker system **1100**, and Figure **5** is a cross-sectional view of the speaker system **1100** taken along chain line C-D shown in Figure **4**.

[0066] The speaker system **1100** includes a display panel **21** for displaying an image, a transparent panel **224** located so as to allow an image displayed in the display panel **21** to be viewed through the transparent panel **224**, a transparent substrate **227** located between the display panel **21** and the transparent panel **224** so as to allow an image displayed in the display panel **21** to be viewed through the substrate **227**, an electric-mechanical-acoustic-transducer **22** having a diaphragm **45** (Figure **2**) for vibrating the diaphragm **45** in accordance with an electric signal so as to output a sound, a spacer (elastic member) **225** for connecting a peripheral portion of the transparent panel **224** and a peripheral portion of the substrate **227**, and a housing **220** for supporting the substrate **227**.

[0067] The speaker system **1100** has a space **226** between the substrate **227** and the transparent panel **224**. The space **226** is preferably a closed space. The substrate **227** has a sound hole **223**. The substrate **227** acts as an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer **22** to the space **226**. The transparent panel **224** can be vibrated by the sound transferred from the electric-mechanical-acoustic-transducer **22** to the space **226** via the sound hole **223**. The substrate **227** supports the transparent panel **224** via the spacer **225**. The transparent panel **224** has an area which is larger than the area of the diaphragm **45**. In this example, the transparent panel **24** is a film which is formed of, for example, PET (polyethylene terephthalate), acrylic resins, or other resin materials transmissive with respect to visible light.

[0068] The electric-mechanical-acoustic-transducer **22** has substantially the same structure as that described in the first example, except that the housing **46** is connected to the substrate **227** such that the diaphragm **45** faces the sound hole **223**.

[0069] An exemplary operation of the speaker system **1100** will be described.

[0070] When an electric signal is applied to the voice coil **44** inserted into the magnetic gap **43**, a driving force is generated in the voice coil **44**. Then, the diaphragm **45** connected to the voice coil **44** is vibrated. Thus, a

sound is generated. The sound generated by the diaphragm 45 is transferred to the space 226 via the sound hole 223. The transparent panel 224 supported by the spacer 225 in the peripheral portion thereof is vibrated by the pressure of the sound transferred to the space 226 and thus generates a sound.

[0071] Figure 6 is a graph illustrating measuring results of a sound pressure vs. frequency characteristic of the speaker system 1100. The measurement was performed as follows. As the electric-mechanical-acoustic-transducer 22, a dynamic speaker having a speaker diameter of 18 mm was used. As the transparent panel 224, a transparent PET plate having a length of 90 mm, a width of 60 mm and a thickness of 0.1 mm was used. A microphone was placed at a position 0.1 m away from the speaker system 1100. A power of 0.1 W was applied to the electric-mechanical-acoustic-transducer 22.

[0072] Characteristic curve III in Figure 6 represents a sound output only from the electric-mechanical-acoustic-transducer 22 in the absence of the transparent panel 224 (comparative example). Characteristic curve IV represents a sound output from the transparent panel 224 (present invention).

[0073] In the dynamic speaker having the speaker diameter of 18 mm used as the electric-mechanical-acoustic-transducer 22, the diaphragm 45 was formed of an acrylic film having a thickness of 20 μ m and a weight of about 6 mg. The voice coil 44 was formed of a copper wire having a diameter of 0.055 mm and a weight of 25 mg. The diameter of the voice coil 44 was 8 mm.

[0074] The transparent panel 224 formed of PET (length: 90 mm; width: 60 mm; thickness: 0.1 mm) weighed about 700 mg. The ratio of the weight of the transparent panel 224 to the total weight of the diaphragm 45 and the voice coil 44 is $700 \text{ mg} / (6 \text{ mg} + 25 \text{ mg}) = \text{about } 22.6 \text{ mg}$. The weight of the transparent panel 224 is about 22.6 times the total weight of the diaphragm 45 and the voice coil 44. Therefore, in the case where the voice coil 44 is connected to the transparent panel 224 (comparative example), the transparent panel 224 cannot be substantially vibrated directly by the voice coil 44. As a result, substantially no sound is generated from the transparent panel 224.

[0075] In the speaker system 1100 in this example, the heavy transparent panel 224 can be sufficiently vibrated by a small force, by the following principle. When the voice coil 44 drives the diaphragm 45 and thus the diaphragm 45 applies a pressure to the space 226, the pressure applied to the space 226 is transferred to the transparent panel 224. Thus, the transparent panel 224 vibrates. Where S_1 is the effective vibration area of the diaphragm 45, S_2 is the vibration area of the transparent panel 224, and M_2 is the weight of the transparent panel 224 (similarly to the first example), the equivalent weight of the transparent panel 224 with respect to the voice coil 44 is $M_2 / (S_2 / S_1)^2$, owing to the effect of the acoustic transformer.

[0076] In the above-described example, the effective vibration area of the diaphragm 45 (S_1) is 98.5 mm and the vibration area of the transparent panel 224 (S_2) is 5400 mm². (As described in the first example, the effective radius of vibration of the diaphragm 45 is 5.6 mm.) The equivalent weight of the transparent panel 224 with respect to the voice coil 44 is $700 \text{ mg} / (5400 \text{ mm}^2 / 98.5 \text{ mm}^2)^2 = 0.2 \text{ mg}$. The sum of the total weight of the diaphragm 45 and the voice coil 44 and the equivalent weight of the transparent panel 224 is $6 \text{ mg} + 25 \text{ mg} + 0.2 \text{ mg} = 31.2 \text{ mg}$. Since the weight of 31.2 mg is substantially the same as total weight of the diaphragm 45 and the voice coil 44 (31 mg), the transparent panel 224 can be sufficiently vibrated by the force generated in the voice coil 44.

[0077] In this manner, the electric-mechanical-acoustic-transducer 22 vibrates the transparent panel 224 via the space 226. Thus, the speaker system 1100, in which the transparent panel 224 having a large area and a great weight is vibrated by a small force as a diaphragm for reproducing an acoustic signal, can be realized.

[0078] The transparent panel 224 and the transparent substrate 227 are transmissive with respect to visible light, and therefore an acoustic signal can be reproduced without the image displayed in the display panel 21 being shielded. The transparent panel 224 is located such that the image displayed in the display panel 21 can be viewed through the transparent panel 224. Therefore, the position where the image is displayed to the user can be the same as the position from which a sound is output to the user. Owing to such a structure, the user does not have any sense of unnaturalness. The system 1100 having such a structure may be mounted on an electronic device or a mobile terminal device (e. g., a personal computer, a TV, a game machine, or a cellular phone) including an image or sound signal processing circuit.

[0079] The substrate 227 is provided between the display panel 21 and the transparent panel 224. Since the substrate 227 protects the display panel 21 against external impacts, the transparent panel 224 can be thinner. Therefore, the acoustic characteristics such as, for example, the reproduction sound volume and the reproduction frequency band can be improved. Especially, the reproduction frequency band in a low frequency range can be expanded.

[0080] During the production process of the speaker system 1100, the space 226 may be formed in advance between the transparent panel 224 and the substrate 227. In this case, precise positioning between the transparent panel 224 and the substrate 227/display panel 21 is not necessary. This simplifies the process for mounting the speaker system 1100 on an electronic device or a mobile terminal device.

[0081] The space 226, surrounded by the transparent panel 224, the substrate 227, the spacer 225 and the electric-mechanical-acoustic-transducer 22, preferably maintains a high level of airtightness in order to prevent

the sound output from the diaphragm **45** from leaking outside. This can be realized by, for example, bonding the transparent panel **224**, the substrate **227**, the spacer **225** and the electric-mechanical-acoustic-transducer **22** together.

[0082] In the second example, a dynamic speaker is used as the electric-mechanical-acoustic-transducer **22**. Alternatively, any type of speaker which outputs a sound from a diaphragm is usable, and substantially the same effect is provided. Exemplary speakers usable include an electromagnetic speaker, a piezoelectric speaker, and a static speaker. The electric-mechanical-acoustic-transducer **22** may be round, elliptic or rectangular. When the electric-mechanical-acoustic-transducer **22** is elliptic or rectangular, the space in which the display panel **21** can be provided is enlarged, i.e., the planar size of the display panel **21** can be increased.

(Example 3)

[0083] A speaker system **1200** according to a third example of the present invention will be described with reference to Figures **7A** and **7B**. Figure **7A** is a plan view of the speaker system **1200**, and Figure **7B** is a cross-sectional view of the speaker system **1200** taken along chain line **E-F** shown in Figure **7A**.

[0084] The speaker system **1200** includes a display panel **21** for displaying an image, a transparent panel **34** located so as to allow an image displayed in the display panel **21** to be viewed through the transparent panel **34**, an electric-mechanical-acoustic-transducer **32** having a diaphragm **52** (Figure **8**) for vibrating the diaphragm **52** in accordance with an electric signal so as to output a sound, an acoustic pipe **33** connected to the electric-mechanical-acoustic-transducer **32**, and a housing **20** for supporting the transparent panel **34** and the display panel **21**.

[0085] The speaker system **1200** has a space **37** between the display panel **21** and the transparent panel **34**. The space **37** is preferably a closed space. The housing **20** is connected to the acoustic pipe **33** via an opening **36** of the acoustic pipe **33**. The acoustic pipe **33** acts as an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer **32** to the space **37**. The transparent panel **34** has a peripheral portion **35** which is thinner than a central portion thereof. The peripheral portion **35** is in the form of a film. The peripheral portion **35** is supported by the housing **20**. The transparent panel **34** can be vibrated by the sound transferred from the electric-mechanical-acoustic-transducer **32** to the space **37** via the acoustic pipe **33**. The transparent panel **34** has an area which is larger than the area of the diaphragm **52**. The transparent panel **34** is formed of glass, an acrylic resin or other materials transmissive with respect to visible light.

[0086] Figure **8** is a cross-sectional view of the electric-mechanical-acoustic-transducer **32**. In this exam-

ple, the electric-mechanical-acoustic-transducer **32** is a piezoelectric speaker, so that the electric-mechanical-acoustic-transducer **32** can be thinner.

[0087] The electric-mechanical-acoustic-transducer **32** includes piezoelectric elements **50** and **51**, the diaphragm **52** having the piezoelectric elements **50** and **51** bonded to both surfaces thereof, a lead **53** connected to an input terminal **57** and the diaphragm **52** for receiving an electric signal, a lead **54** connected to an input terminal **56** and the piezoelectric element **51**, a lead **55** connected to the input terminal **56** and the piezoelectric element **50**, and a housing **58** for supporting a peripheral portion of the diaphragm **52**. The diaphragm **52** contains a conductive material of phosphor bronze, stainless steel or the like, and acts as an intermediate electrode. The housing **58** is connected to the acoustic pipe **33**.

[0088] An exemplary operation of the speaker system **1200** will be described.

[0089] When an electric signal is applied to the input terminals **56** and **57**, the piezoelectric elements **50** and **51** bonded on both surfaces of the diaphragm **52** are warped, and a sound is generated from the diaphragm **52** and the piezoelectric elements **50** and **51**. The sound passes through the acoustic pipe **33** and is transferred to the space **37** via the opening **36**. The transparent panel **34** supported by the housing **20** in the peripheral portion thereof is driven and vibrated by the pressure of the sound transferred to the space **37** and thus generates a sound. This manner of sound generation by the transparent panel **34** is substantially the same as that by the transparent panel **24** in the first example.

[0090] The speaker system **1200** in the third example is different from the speaker system **1000** in the first example in that the speaker system **1200** uses the acoustic pipe **33** as the acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer **32** to the space **37**. Such a structure allows the electric-mechanical-acoustic-transducer **32** to be provided closer to a bottom surface of the housing **20** with respect to the display panel **21**. This increases a space in which the display panel **21** can be provided; i.e., increases the planar size of the display panel **21**.

[0091] The opening **36** of the acoustic pipe **33** may have a rectangular shape, so that one of the sides of the display panel **21** which is adjacent to the opening **36** is parallel to the longitudinal direction of the opening **36**. In this case, the planar size of the display panel **21** can be further increased.

[0092] The peripheral portion **35** of the transparent panel **34** may be integrally formed of the same material as that of the central portion of the transparent panel **34**, or may be formed of a different material from that of the central portion of the transparent panel **34** and fixed to the central portion of the transparent panel **34**.

[0093] The transparent panel **34** may be formed of a film entirely in addition to the peripheral portion **35**. In this case, the entirety of the transparent panel **34** is driv-

en by the sound output from the electric-mechanical-acoustic-transducer **32**.

[0094] In the third example, a piezoelectric speaker is used as the electric-mechanical-acoustic-transducer **32**. Alternatively, any type of speaker which outputs a sound from a diaphragm is usable, and substantially the same effect is provided. Exemplary speakers usable include an electromagnetic speaker, a dynamic speaker, and a static speaker.

[0095] Next, a speaker system **1300** as a modification example of the speaker system **1100** in the second example of the present invention will be described with reference to Figures **9A** and **9B**. Figure **9A** is a plan view of the speaker system **1300**, and Figure **9B** is a cross-sectional view of the speaker system **1300** taken along chain line **G-H** shown in Figure **9A**.

[0096] The speaker system **1300** includes the electric-mechanical-acoustic-transducer **32** and the acoustic pipe **33** connected to the electric-mechanical-acoustic-transducer **32**, instead of the electric-mechanical-acoustic-transducer **22**. The sound hole **223** of the substrate **227** is communicated to the opening **36** of the acoustic pipe **33**. The acoustic pipe **33** acts as an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer **32** to the space **37**.

[0097] An exemplary operation of the speaker system **1300** will be described.

[0098] When an electric signal is applied to the input terminals **56** and **57**, the piezoelectric elements **50** and **51** bonded on both surfaces of the diaphragm **52** are warped, and a sound is generated from the diaphragm **52** and the piezoelectric elements **50** and **51**. The sound passes through the acoustic pipe **33** and is transferred to the space **226** via the opening **36**. The transparent panel **224** is vibrated by the pressure of the sound transferred to the space **226** and thus generates a sound.

[0099] The speaker system **1300** uses the acoustic pipe **33** as the acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer **32** to the space **226**. Such a structure allows the electric-mechanical-acoustic-transducer **32** to be provided closer to a bottom surface of the housing **220** with respect to the display panel **21**. This increases a space in which the display panel **21** can be provided; i.e., increases the planar size of the display panel **21**.

[0100] The opening **36** of the acoustic pipe **33** may have a rectangular shape, so that one of the sides of the display panel **21** which is adjacent to the opening **36** is parallel to the longitudinal direction of the opening **36**. In this case, the planar size of the display panel **21** can be further increased.

[0101] In this example, a piezoelectric speaker is used as the electric-mechanical-acoustic-transducer **32**. Alternatively, any type of speaker which outputs a sound from a diaphragm is usable, and substantially the same effect is provided. Exemplary speakers usable in-

clude an electromagnetic speaker, a dynamic speaker, and a static speaker.

(Example 4)

[0102] A speaker system **1400** according to a fourth example of the present invention will be described with reference to Figures **10A** and **10B**. Figure **10A** is a plan view of the speaker system **1400**, and Figure **10B** is a cross-sectional view of the speaker system **1400** taken along chain line **I-J** shown in Figure **10A**. The speaker system **1400** basically has the structure of the speaker system **1200** in the third example with a plurality of electric-mechanical-acoustic-transducers.

[0103] The speaker system **1400** includes a display panel **21** for displaying an image, a transparent panel **138** located so as to allow an image displayed in the display panel **21** to be viewed through the transparent panel **138**, electric-mechanical-acoustic-transducers **32** and **132** each having a diaphragm **52** (Figure **8**) for vibrating the diaphragm **52** in accordance with an electric signal so as to output a sound, acoustic pipes **33** and **133**, and a housing **130** for supporting the transparent panel **138**, respectively connected to the electric-mechanical-acoustic-transducer **32** and **132**, and the display panel **21**.

[0104] The speaker system **1400** has a space **139** between the display panel **21** and the transparent panel **138**. The space **139** is preferably a closed space. The housing **130** is connected to the acoustic pipe **33** via an opening **36** thereof and to the acoustic pipe **133** via an opening **136** thereof. The acoustic pipes **33** and **133** each act as an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducers **32** and **132** to the space **139**. The transparent panel **138** is supported by the housing **130** in a peripheral portion thereof, and can be vibrated by the sound transferred from the electric-mechanical-acoustic-transducers **32** and **132** to the space **139**. The transparent panel **138** has an area which is larger than the area of the diaphragm **52**. In this example, the transparent panel **138** is a film which is formed of, for example, PET (polyethylene terephthalate), or other resin materials transmissive with respect to visible light.

[0105] An exemplary operation of the speaker system **1400** will be described.

[0106] The speaker system **1400** in the fourth example is different from the speaker system **1200** in the third example in that the speaker system **1400** includes the plurality of electric-mechanical-acoustic-transducers **32** and **132** and the plurality of acoustic pipes **33** and **133**. The transparent panel **138** is entirely a film.

[0107] The electric-mechanical-acoustic-transducer **132** has the same structure as that of the electric-mechanical-acoustic-transducer **32** described in the third example. The electric-mechanical-acoustic-transducer **132** also operates in the same manner as the electric-mechanical-acoustic-transducer **32** described in the

third example. The acoustic pipes **33** and **133** are respectively connected to the electric-mechanical-acoustic-transducers **32** and **132**. The openings **36** and **136** of the acoustic pipes **33** and **133** are communicated with the space **139** at different positions from each other. The sound output from the electric-mechanical-acoustic-transducer **132** is transferred to the space **139** via the acoustic pipe **133**. The transparent panel **138** is vibrated by the pressure of the sound transferred to the space **139** so as to generate a sound.

[0108] When, for example, an electric signal representing information for a right channel is input to the electric-mechanical-acoustic-transducer **32** and an electric signal representing information for a left channel is input to the electric-mechanical-acoustic-transducer **132**, the sound for the right channel is transferred to the space **139** via the opening **36** and the sound for the left channel is transferred to the space **139** via the opening **136**. Thus, the transparent panel **138** is vibrated by a synthesis sound pressure for the right and left channels. In this manner, a stereo reproduction is realized. Especially because the transparent panel **138** is a film in this example, portions of the transparent panel **138** which are immediately facing the openings **36** and **136** are vibrated by a sound of a high frequency range which has a short wavelength and narrow directivity. The entire transparent panel **138** is vibrated by a sound of a low frequency range which has a long wavelength and wide directivity. Even though the sound for the right channel and the sound for the left channel are synthesized in the space **139**, the sound of the high frequency range which contributes to the expansion of the sound image is output from separate positions of the transparent panel **138**. Thus, an effective stereo reproduction is realized by one transparent panel **138**.

[0109] In the case where the speaker system **1400** is mounted on a mobile terminal device including a relatively large display panel such as, for example, a PDA (personal digital assistant), the openings **36** and **136** of the acoustic pipes **33** and **133** can be located on both ends of the display panel **21**, i.e. away from each other by a relatively large distance. Therefore, a sound image of the sound output from the display panel **21** is enlarged, and thus a more effective stereo reproduction is provided.

[0110] The speaker system **1400** includes two electric-mechanical-acoustic-transducers **32** and **132** in this example, but may include three or more electric-mechanical-acoustic-transducers. Each of the plurality of electric-mechanical-acoustic-transducers is connected to an acoustic pipe. Each acoustic pipe is communicated to the space **139** at different positions. In this case, the transparent panel **138** is vibrated by the plurality of electric-mechanical-acoustic-transducers, and therefore a sound of a higher volume is output from the transparent panel **138**.

[0111] The display panel **21** may have an opening at top, bottom, right and left positions thereof. In this case,

for example, the openings on the top and bottom positions may be used to transfer the sound output from the electric-mechanical-acoustic-transducer based on an electric signal representing audio information for one of multiple channels. Thus, a more realistic sound can be reproduced.

[0112] When the electric signal is a monaural signal, the same electric signal may be input to the plurality of electric-mechanical-acoustic-transducers. Alternatively, the monaural signal may be input to one of the electric-mechanical-acoustic-transducers.

[0113] An electric-mechanical-acoustic-transducer **232** shown in Figure **11** may be used instead of the electric-mechanical-acoustic-transducer **32**. The electric-mechanical-acoustic-transducer **232** includes a cup-shaped yoke **140** having a spindle section **141** along a periphery thereof, a magnet **41** provided on a central part of the yoke **140**, a plate **42** provided on a top surface of the magnet **41**, a voice coil **44** inserted into a magnetic gap **144** between the yoke **140** and the plate **42**, a diaphragm **45** connected to the voice coil **44**, housings **147** and **247** for supporting a peripheral portion of the diaphragm **45**, and a suspension **148** connected to a peripheral portion of the yoke **140** and a bottom surface of the housing **147**. The housing **247** is connected to the acoustic pipe **33**. A magnetic circuit **142** includes the yoke **140**, the magnet **41**, and the plate **42**. Since the magnetic circuit **142** is supported by the suspension **148**, the magnetic circuit **142** can be vibrated so as to generate a mechanical vibration simultaneously with, or independent from, the acoustic signal reproduction.

[0114] The electric-mechanical-acoustic-transducer **232** outputs a sound from the diaphragm **45** as described in the first example with reference to Figure **2**.

[0115] An exemplary operation of the magnetic circuit **142** for generating a mechanical vibration will be described. A vibration function of an electric-mechanical-acoustic-transducer is disclosed by, for example, Japanese Laid-Open Publication No. 10-215499 and will not be described in detail here. When an electric signal is applied to the voice coil **44**, a force is generated in the magnetic circuit **142** in the opposite direction to the force generated in the voice coil **44**. The magnetic circuit **142** is supported by the housing **147** via the suspension **148**.

A mechanical resonating system includes the mass of the magnetic circuit **142** and the stiffness of the suspension **148**. When the frequency of the electric signal applied to the voice coil **44** substantially matches the resonating frequency of the mechanical resonating system, the magnetic circuit **142** largely vibrates. This vibration is transferred to the housing **147** via the suspension **148**. Since the housing **147** is mechanically coupled to the housing **130** via the housing **247** and the acoustic pipe **33**, the vibration of the magnetic circuit **142** is transferred to the housing **130** so as to vibrate the housing **130**.

[0116] As described above, the electric-mechanical-acoustic-transducer **232** has two functions of acoustic

signal reproduction and generation of a mechanical vibration. For example, the speaker system **1400** may be used for a mobile terminal device having a signal receiving function, for example, a cellular phone. In this case, the mobile terminal device has both a function of a speaker of notifying the user of the signal reception by an acoustic signal of a melody or the like, and a function of a vibrator of notifying the user of the signal reception by a vibration transferred to the body of the user.

[0117] When an electronic device including the speaker system **1400** including the electric-mechanical-acoustic-transducer **232** is used to play a game or the like, the combination of a realistic sound effect and a vibration transferred to the user raise the level of excitement of the game.

[0118] Even when the electric signal is a monaural signal, the user feels the vibration in addition to hearing the acoustic signal reproduced from the same plane of the transparent panel **138**.

[0119] The electric-mechanical-acoustic-transducer **232** may be used instead of the electric-mechanical-acoustic-transducer **132**. In the first through third examples, the electric-mechanical-acoustic-transducer **232** may be used instead of each of the electric-mechanical-acoustic-transducers **22** and **32**.

[0120] Next, a speaker system **1500** as a modification example of the speaker system **1100** in the second example of the present invention will be described with reference to Figure 12.

[0121] The speaker system **1500** includes the electric-mechanical-acoustic-transducer **32** and the acoustic pipe **33** shown in Figure **9B** in addition to the structure of the speaker system **1100**. The acoustic pipe **33** is connected to the electric-mechanical-acoustic-transducer **32**. A substrate **127**, which is provided instead of the substrate **227**, has sound holes **123** and **323**. The electric-mechanical-acoustic-transducer **22** is connected to the substrate **127** via the sound hole **123**, and the opening **36** of the acoustic pipe **33** is communicated to the sound hole **323**. In this example, the transparent panel **224** is formed of a film. A space **126** is formed between the substrate **127** and the transparent panel **224**. The space **126** is preferably a closed space.

[0122] An exemplary operation of the speaker system **1500** will be described.

[0123] The electric-mechanical-acoustic-transducers **22** and **32** operate as described in the first and third examples. The sound output from the electric-mechanical-acoustic-transducer **22** is transferred to the space **126** via the sound hole **123**. The sound output from the electric-mechanical-acoustic-transducer **32** is transferred to the space **126** via the acoustic pipe **33**. The transparent panel **224** is vibrated by the pressure of the sound transferred to the space **126** so as to generate a sound.

[0124] When, for example, an electric signal representing information for a right channel is input to the electric-mechanical-acoustic-transducer **22** and an electric signal representing information for a left channel

is input to the electric-mechanical-acoustic-transducer **32**, the sound for the right channel is transferred from the electric-mechanical-acoustic-transducer **22** to the space **126** and the sound for the left channel is transferred from the electric-mechanical-acoustic-transducer **32** to the space **126**. Thus, the transparent panel **224** is vibrated by a synthesis sound pressure for the right and left channels. In this manner, a stereo reproduction is realized. Especially because the transparent panel **224** is a film in this example, portions of the transparent panel **224** which are immediately facing the openings **123** and **323** are vibrated by a sound of a high frequency range which has a short wavelength and narrow directivity. The entire transparent panel **224** is vibrated by a sound of a low frequency range which has a long wavelength and wide directivity. Even though the sound for the right channel and the sound for the left channel are synthesized in the space **126**, the sound of the high frequency range which contributes to the expansion of the sound image is output from separate positions of the transparent panel **224**. Thus, an effective stereo reproduction is realized by one transparent panel **224**.

[0125] In the case where the acoustic pipe **33** is connected to the electric-mechanical-acoustic-transducer **32** at a position off the center of the electric-mechanical-acoustic-transducer **32**, the electric-mechanical-acoustic-transducer **32** can be efficiently provided in an empty space in the housing **220**. The empty space in the housing **220** can also be efficiently formed in the housing **220**. In this empty space, an electric circuit such as, for example, a signal receiving circuit, can be provided as well as the electric-mechanical-acoustic-transducer **32**.

[0126] The electric-mechanical-acoustic-transducers **22** and **32** may both be a dynamic speaker or a piezoelectric speaker.

[0127] An electric-mechanical-acoustic-transducer **232** may be used instead of each of the electric-mechanical-acoustic-transducers **22** and **32**.

[0128] An acoustic pipe may be provided between the electric-mechanical-acoustic-transducer **22** and the sound hole **123**. The electric-mechanical-acoustic-transducer **32** may be directly connected to the substrate **127** with the acoustic pipe **33** being omitted.

[0129] The speaker system **1500** in this example includes two electric-mechanical-acoustic-transducers **22** and **32** and one acoustic pipe **33**. The speaker system **1500** may include three or more electric-mechanical-acoustic-transducers and three or more acoustic pipe.

[0130] The electric-mechanical-acoustic-transducers **22**, **32** and **132** each may be a dynamic speaker, an electromagnetic speaker, a piezoelectric speaker, a static speaker or any type of speaker which outputs a sound from a diaphragm.

[0131] In the speaker systems **1400** and **1500**, the electric signal represents at least one of a received sound, a call arrival sound, and audio information for a plurality of channels. When the electric signal repre-

sents at least one of the received sound and the call arrival sound, the electric signal is input to the plurality of electric-mechanical-acoustic-transducers **22**, **32** and **132**. When the electric signal represents the audio information for the plurality of channels, an electric signal representing audio information for each of the plurality of channels is input to a respective one of the electric-mechanical-acoustic-transducers **22**, **32** and **132**.

(Example 5)

[0132] A mobile terminal device **2000** according to a fifth example of the present invention will be described with reference to Figures **13** and **14**. Figure **13** is a partially cut plan view of the mobile terminal device **2000**. Figure **14** is a block diagram illustrating an internal structure of the mobile terminal device **2000**.

[0133] In this example, the mobile terminal device **2000** is described as a cellular phone. However, the mobile terminal device **2000** is not limited to a cellular phone. The mobile terminal device **2000** may be, for example, a PDA, a beeper, or a wristwatch.

[0134] The mobile terminal device **2000** includes a first housing **100**, a second housing **101** including, for example, a built-in signal receiving circuit, a signal receiving antenna **102** attached to the second housing **101**, and a speaker system **1201**. The first housing **100** includes an electric circuit, a connector and the like (not shown) built therein. The speaker system **1201** is a modification example of the speaker system **1200** described in the third example. The speaker system **1201** includes a display panel **221** instead of the display panel **21** included in the speaker system **1200**. The display panel **221** is, for example, a liquid crystal display, and has a function similar to that of the display **21**. In the speaker system **1201**, the display panel **221** and a peripheral portion **35** of the transparent panel **34** are supported by the second housing **101**. The speaker system **1201** includes a space **237** between the display panel **221** and the transparent panel **34**. The space **237** is preferably a closed space. The display panel **221** is supported by the second housing **101** such that an image displayed in the display panel **221** can be viewed from outside.

[0135] An exemplary operation of the mobile terminal device **2000** will be described.

[0136] The operation of the speaker system **1201** is substantially the same as that of the speaker system **1200** described in the third example.

[0137] When an electric signal representing a received sound (for example, the voice of a caller) is applied to the electric-mechanical-acoustic-transducer **32** (Figure **14**), the received sound is reproduced from the transparent panel **34**. In this case, the speaker system **1201** acts as a receiver, which is a speaker for reproducing the received sound.

[0138] When an electric signal representing, for example, a call arrival sound, music, voice or a sound effect for a game is applied to the electric-mechanical-

acoustic-transducer **32**, the call arrival sound, the music, the voice or the sound effect for the game is reproduced from the transparent panel **34**. In this case, the speaker system **1201** acts as a loudspeaker.

[0139] In the case where the mobile terminal device **2000** is a telephone having a function of, for example, a video telephone, an image signal is applied to the display panel **221** so as to display the face of a person on the other end in the display panel **221**, and concurrently the voice of the person represented by a voice signal is reproduced from the transparent panel **34**.

[0140] As in the first example, the speaker system **1201** according to the present invention can sufficiently vibrate the transparent panel **34** having a large area and a great weight by a small force. Accordingly, even when the display panel **221** of the mobile terminal device **2000** has a large area and thus the transparent panel **34** also has a large area, the transparent panel **34** can be sufficiently vibrated. In addition, the surface from which the sound is output is the same as the surface on which the image is displayed. Therefore, the position where the image is displayed to the user can be the same as the position from which the sound is output to the user. Thus, a more realistic acoustic signal reproduction is realized. Such a mobile terminal device **2000** is optimum for simultaneously reproducing the sound and the image.

[0141] When the transparent panel **34** operates as a diaphragm of the receiver for reproducing a received sound, the received sound is reproduced from the entire surface of the transparent panel **34**. Therefore, at whichever position of the large transparent panel **34** the user's ear may contact, the user can hear the sound. Since it is not necessary to put the user's ear at a particular position, the user's ear is never deviated from the sound source. Such a mobile terminal device **2000** allows especially an aged user to easily hear the received sound.

[0142] The operation of the mobile terminal device **2000** will be further described with reference to Figure **14**.

[0143] The mobile terminal device **2000** includes a signal output section **120** for outputting an electric signal based on a wireless signal received by the antenna **102**. The signal output section **120** includes a wireless signal processing section **121** and an electric signal amplification section **122**.

[0144] The antenna **102** receives a wireless signal externally sent (for example, sent from a relay station for cellular phones). The wireless signal represents a call arrival sound, a received sound, music, an image or the like.

[0145] When the antenna **102** receives a wireless signal representing a call arrival sound, the wireless signal processing section **121** outputs a call arrival sound signal representing the call arrival sound so as to notify the user of a call arrival. The call arrival sound signal is amplified by the electric signal amplification section **122** and applied to the electric-mechanical-acoustic-trans-

ducer **32**, and the transparent panel **34** reproduces the call arrival sound. The call arrival sound signal may be a signal representing a preset call sound or an audio signal obtained by data distribution or the like. When the user learns of the call arrival and puts the mobile terminal device **2000** into a call receivable state, the wireless signal processing section **121** outputs a received sound signal representing a received sound (for example, the voice of the caller). The received sound signal is amplified by the electric signal amplification section **122** and applied to the electric-mechanical-acoustic-transducer **32**. Thus, the transparent panel **34** reproduces the received sound.

[0146] In this case, the user can select one of two methods of using the mobile terminal device **2000**: (i) a method of putting his/her ear into contact with the transparent panel **34** as in a general cellular phone; and (ii) a method of using the mobile terminal device **2000** in a hands free mode, from a position away from the mobile terminal device **2000**. In the hands free mode, the amplification ratio of the electric signal amplification section **122** is increased so as to raise the reproduction sound volume. Also in the hands free mode, when both of the telephones (telephones of the caller and the user) include a camera so as to provide a function of a video telephone, the caller and the user can talk while seeing each other's face on the display panel **221** based on the image signal. The image signal represents a moving picture, a still picture, character information or other images. When the antenna **102** receives a wireless signal representing an image and the wireless signal output section **121** outputs an image signal to the display panel **221**, the image is displayed in the display panel **221**.

[0147] In the case where the mobile terminal device **2000** is used in a hands free mode, the speaker system **1201** acts as a loudspeaker. Use of the mobile terminal device **2000** as the loudspeaker realizes, for example, reproduction of a music signal downloaded through the Internet.

[0148] The function of the mobile terminal device **2000** of simultaneously reproducing an image and a sound is effective for, for example, reproducing a promotional video of a music tune or using the mobile terminal device **2000** as a game machine.

[0149] The mobile terminal device **2000** may include the speaker system **1000** in the first example instead of the speaker system **1201**.

(Example 6)

[0150] A mobile terminal device **2100** according to a sixth example of the present invention will be described with reference to Figures **15** and **16**. Figure **15** is a partially cut plan view of the mobile terminal device **2100**. Figure **16** is a block diagram illustrating an internal structure of the mobile terminal device **2100**.

[0151] In this example, the mobile terminal device **2100** is described as a cellular phone. However, the mo-

bile terminal device **2100** is not limited to a cellular phone.

[0152] The mobile terminal device **2100** includes a first housing **100**, a second housing **101** including, for example, a built-in signal receiving circuit, a signal receiving antenna **102** attached to the second housing **101**, and a speaker system **1301**. The first housing **100** includes an electric circuit, a connector and the like (not shown) built therein. The speaker system **1301** is a modification example of the speaker system **1300** described in the third example. The speaker system **1301** includes a display panel **221** instead of the display panel **21** included in the speaker system **1300**. In the speaker system **1301**, the display panel **221** is supported by the second housing **101** such that an image displayed in the display panel **221** can be viewed from outside.

[0153] An exemplary operation of the mobile terminal device **2100** will be described. The mobile terminal device **2100** is different from the mobile terminal device **2000** in that the mobile terminal device **2100** includes the speaker system **1301** instead of the speaker system **1201** included in the mobile terminal device **2000**. The structure of the mobile terminal device **2100** is substantially the same as that of the mobile terminal device **2000** except for the speaker system, and operates in substantially the same manner as the mobile terminal device **2000**. The speaker system **1301** includes the substrate **227**. The substrate **227** provides the effect as described in the third example. The operation of the speaker system **1301** is substantially the same as that of the speaker system **1300** described in the third example.

[0154] When an electric signal representing a received sound is applied to the electric-mechanical-acoustic-transducer **32** (Figure **16**), the received sound is reproduced from the transparent panel **224**. In this case, the speaker system **1301** acts as a receiver, which is a speaker for reproducing the received sound.

[0155] When an electric signal representing, for example, a call arrival sound, music, voice or a sound effect for a game is applied to the electric-mechanical-acoustic-transducer **32**, the call arrival sound, the music, the voice or the sound effect for the game is reproduced from the transparent panel **224**. In this case, the speaker system **1301** acts as a loudspeaker.

[0156] In the case where the mobile terminal device **2100** is a telephone having a function of, for example, a video telephone, an image signal is applied to the display panel **221** so as to display the face of a person on the other end in the display panel **221**, and concurrently the voice of the person represented by a voice signal is reproduced from the transparent panel **224**.

[0157] The operation of the mobile terminal device **2100** will be further described with reference to Figure **16**.

[0158] The mobile terminal device **2100** includes a signal output section **120** for outputting an electric signal based on a wireless signal received by the antenna **102**. The signal output section **120** includes a wireless signal

processing section **121** and an electric signal amplification section **122**. The operation of the mobile terminal device **2100** of receiving a wireless signal and driving the speaker system **1301** is substantially the same as that of the mobile terminal device **2000**.

[0159] The mobile terminal device **2100** may include the speaker system **1000** in the first example instead of the speaker system **1301**.

[0160] In this example, the mobile terminal device including a speaker system according to the present invention is described. A speaker system according to the present invention is applicable to an electronic device having a display panel, for example, a TV, a personal computer, a game machine, or a car navigation system.

(Example 7)

[0161] A mobile terminal device **2200** according to a seventh example of the present invention will be described with reference to Figures **17** and **18**. Figure **17** is a partially cut plan view of the mobile terminal device **2200**. Figure **18** is a block diagram illustrating an internal structure of the mobile terminal device **2200**.

[0162] In this example, the mobile terminal device **2200** is described as a cellular phone. However, the mobile terminal device **2200** is not limited to a cellular phone.

[0163] The mobile terminal device **2200** includes a first housing **100**, a second housing **101** including, for example, a built-in signal receiving circuit, a signal receiving antenna **102** attached to the second housing **101**, and a speaker system **1501**. The first housing **100** includes an electric circuit, a connector and the like (not shown) built therein. The speaker system **1501** is a modification example of the speaker system **1500** described in the fourth example. The speaker system **1501** includes a display panel **221** instead of the display panel **21** included in the speaker system **1500**. In the speaker system **1501**, the display panel **221** and the substrate **227** are supported by the second housing **101**. The display panel **221** is supported by the second housing **101** such that an image displayed in the display panel **221** can be viewed from outside.

[0164] An exemplary operation of the mobile terminal device **2200** will be described.

[0165] The operation of the speaker system **1501** is substantially the same as that of the speaker system **1500** described in the fourth example.

[0166] When an electric signal representing a received sound is applied to at least one of the electric-mechanical-acoustic-transducers **22** and **32** (Figure **18**), the received sound is reproduced from the transparent panel **224**. In this case, the speaker system **1501** acts as a receiver, which is a speaker for reproducing the received sound.

[0167] When an electric signal representing, for example, a call arrival sound, music, voice or a sound effect for a game is applied to at least one of the electric-

mechanical-acoustic-transducers **22** and **32**, the call arrival sound, the music, the voice or the sound effect for the game is reproduced from the transparent panel **224**. In this case, the speaker system **1501** acts as a loudspeaker.

[0168] When the same electric signal is applied to the electric-mechanical-acoustic-transducers **22** and **32**, the sound pressure level can be improved as compared to the sound pressure level obtained by a speaker system including one electric-mechanical-acoustic-transducer, with a given power consumption. As described above, the speaker system **1501** can reproduce audio signals for a plurality of channels. For, for example, reproducing audio signals representing music in stereo, a music signal for the right channel is applied to the electric-mechanical-acoustic-transducer **22** and a music signal for the left channel is applied to the electric-mechanical-acoustic-transducer **32**. Thus, the music is reproduced in stereo from the transparent panel **224**.

[0169] In the case where the mobile terminal device **2200** is a telephone having a function of, for example, a video telephone, an image signal is applied to the display panel **221** so as to display the face of a person on the other end in the display panel **221**, and concurrently the voice of the person represented by a voice signal is reproduced from the transparent panel **224**.

[0170] As in the first example, the speaker system **1501** according to the present invention can sufficiently vibrate the transparent panel **224** having a large area and a great weight by a small force. Accordingly, even when the display panel **221** of the mobile terminal device **2200** has a large area and thus the transparent panel **224** also has a large area, the transparent panel **224** can be sufficiently vibrated. In addition, the surface from which the sound is output is the same as the surface on which the image is displayed. Therefore, the position where the image is displayed to the user can be the same as the position from which the sound is output to the user. Thus, a more realistic acoustic signal reproduction is realized.

[0171] The operation of the mobile terminal device **2200** will be further described with reference to Figure **18**.

[0172] The mobile terminal device **2200** includes a signal output section **320** for outputting an electric signal based on a wireless signal received by the antenna **102**. The signal output section **320** includes a wireless signal processing section **121** and electric signal amplification sections **122** and **222**.

[0173] The antenna **102** receives a wireless signal externally sent (for example, sent from a relay station for cellular phones). The wireless signal represents a call arrival sound, a received sound, music, an image or the like.

[0174] When the antenna **102** receives a wireless signal representing a call arrival sound, the wireless signal processing section **121** outputs a call arrival sound signal representing the call arrival sound so as to notify the

user of a call arrival. The call arrival sound signal is amplified by at least one of the electric signal amplification sections **122** and **222** and applied to at least one of the electric-mechanical-acoustic-transducers **22** and **32**, and the transparent panel **224** reproduces the call arrival sound. The call arrival sound signal may be a signal representing a preset call sound or an audio signal obtained by data distribution or the like. When the call arrival sound signal is input in the form of stereo audio signals, the audio signal for the right channel is amplified by the electric signal amplification section **122** and applied to the electric-mechanical-acoustic-transducer **22**, and the audio signal for the left channel is amplified by the electric signal amplification section **222** and applied to the electric-mechanical-acoustic-transducer **32**. Thus, the transparent panel **34** reproduces a stereo sound. When the user learns of the call arrival and puts the mobile terminal device **2200** into a call receivable state, the wireless signal processing section **121** outputs a received sound signal representing a received sound (for example, the voice of the caller). The received sound signal is amplified by at least one of the electric signal amplification sections **122** and **222** and applied to at least one of the electric-mechanical-acoustic-transducers **22** and **32**. Thus, the transparent panel **224** reproduces the received sound.

[0175] In this case, the user can select one of two methods of using the mobile terminal device **2200**: (1) a method of putting his/her ear into contact with the transparent panel **224** as in a general cellular phone; and (ii) a method of using the mobile terminal device **2200** in a hands free mode, from a position away from the mobile terminal device **2200**. In the hands free mode, the amplification ratio of the electric signal amplification sections **122** and **222** is increased so as to raise the reproduction sound volume. Also in the hands free mode, when both of the telephones (telephones of the caller and the user) include a camera so as to provide a function of a video telephone, the caller and the user can talk while seeing each other's face on the display panel **221** based on the image signal. The image signal represents a moving picture, a still picture, character information or other images. When the antenna **102** receives a wireless signal representing an image and the signal output section **320** outputs an image signal to the display panel **221**, the image is displayed in the display panel **221**.

[0176] In the case where the mobile terminal device **2200** is used in a hands free mode, the speaker system **1501** acts as a loudspeaker. Use of the mobile terminal device **2200** as the loudspeaker realizes, for example, reproduction of a music signal downloaded through the Internet.

[0177] The function of the mobile terminal device **2200** of simultaneously reproducing an image and a sound is effective for, for example, reproducing a promotional video of a music tune or using the mobile terminal device **2200** as a game machine.

[0178] In the mobile terminal device **2200**, the electric signal represents at least one of a received sound, a call arrival sound, and audio information for a plurality of channels. When the electric signal represents at least one of the received sound and the call arrival sound, the electric signal is input to the plurality of electric-mechanical-acoustic-transducers **22** and **32**. When the electric signal represents the audio information for the plurality of channels, an electric signal representing audio information for each of the plurality of channels is input to a respective one of the electric-mechanical-acoustic-transducers **22** and **32**.

[0179] The mobile terminal device **2200** may include the speaker system **1400** in the fourth example instead of the speaker system **1501**. In this case, the operation of the speaker system **1400** is substantially the same as that of the speaker system **1501**.

[0180] In this example, the mobile terminal device including a speaker system according to the present invention is described. A speaker system according to the present invention is applicable to an electronic device having a display panel, for example, a TV, a personal computer, a game machine, or a car navigation system.

(Example 8)

[0181] A mobile terminal device **2300** according to an eighth example of the present invention will be described with reference to Figures **19A**, **19B**, **19C** and **20**. Figure **19A** is a partially cut plan view of the mobile terminal device **2300**. Figure **19B** is a partially cut side view of the mobile terminal device **2300**. Figure **19C** is a bottom view of the mobile terminal device **2300**.

[0182] In this example, the mobile terminal device **2300** is described as a cellular phone. However, the mobile terminal device **2300** is not limited to a cellular phone.

[0183] The mobile terminal device **2300** includes a first housing **100**, a second housing **201**, a signal receiving antenna **102** attached to the second housing **201**, and a speaker system **1600**. The speaker system **1600** is a modification example of the speaker system **1300** described in the third example. The speaker system **1600** includes an electric-mechanical-acoustic-transducer **322** instead of the electric-mechanical-acoustic-transducer **32**. In the speaker system **1600**, the display panel **221** and the substrate **227** are supported by the second housing **201**. The second housing **201** has a sound hole **423**. The second housing **201** includes an electric circuit, a connector and the like (not shown) built therein.

[0184] With reference to Figure **20**, the electric-mechanical-acoustic-transducer **322** will be described. The electric-mechanical-acoustic-transducer **322** includes a cylindrical first magnet **520**, an annular second magnet **521** provided so as to surround the first magnet **520**, a yoke **522** for connecting the first magnet **520** and the second magnet **521**, a first voice coil **527** provided in a

first magnetic gap **525** between the first magnet **520** and the yoke **522**, a second voice coil **528** provided in a second magnetic gap **526** between the second magnet **521** and the yoke **522**, a first diaphragm **529** connected to the first voice coil **527**, a second diaphragm **530** provided oppositely to the diaphragm **529** with respect to the first magnet **520** and connected to the second voice coil **528**, a disc-shaped first magnetic plate **523** provided between the first diaphragm **529** and the first magnet **520**, an annular second magnetic plate **524** provided between the second diaphragm **530** and the second magnet **521**, a first housing **531** for supporting the first diaphragm **529**, the second diaphragm **530** and the second magnet **521**, and a second housing **532** for covering the first diaphragm **529** provided oppositely to the diaphragm **529** with respect to the first magnet **520**. The second housing **532** is connected to the acoustic pipe **33**.

[0185] An exemplary operation of the electric-mechanical-acoustic-transducer **322** will be described.

[0186] When an electric signal is applied to the first voice coil **527** inserted into the first magnetic gap **525**, a driving force is generated in the first voice coil **527**. Then, the first diaphragm **529** connected to the first voice coil **527** is vibrated so as to generate a sound. Similarly, when an electric signal is applied to the second voice coil **528** inserted into the second magnetic gap **526**, a driving force is generated in the second voice coil **528**. Then, the second diaphragm **530** connected to the second voice coil **528** is vibrated so as to generate a sound.

[0187] The sound output from the first diaphragm **529** is transferred to the space **226** via the acoustic pipe **33**, and thus the sound is output from the transparent panel **224**. The sound output from the second diaphragm **530** is transferred outside the mobile terminal device **2300** via the sound hole **423** (Figure **19B**).

[0188] In the electric-mechanical-acoustic-transducer **322**, the first voice coil **527** inserted into the first magnetic gap **525** is driven using the first magnet **520**, and the second voice coil **528** inserted into the second magnetic gap **526** is driven using the second magnet **521**. Since the first and second magnets **527** and **528** are driven by different magnets, the driving force generated in each of the first and second voice coils **527** and **528** can be increased. Thus, the electric-mechanical-acoustic-transducer **322** can generate a sound having a large volume.

[0189] The first voice coil **527** and the second voice coil **528** are independently drivable from each other. A call arrival sound or a received sound which is output from the first diaphragm **529** is transferred to the space **226** via the acoustic pipe **33**. Thus, the call arrival sound or the received sound is output from the transparent panel **224**. The housing **100** and the second housing **101** can be folded with respect to each other along a connection section **200**. When the mobile terminal device **2300** is open (i.e., when the housing **100** and the

second housing **101** are not folded with respect to each other), the user can clearly hear the call arrival sound output from the transparent panel **224**. By contrast, when the mobile terminal device **2300** is closed (i.e., when the housing **100** and the second housing **101** are folded with respect to each other), the call arrival sound output from the transparent panel **224** is shielded by the first housing **100**, making it difficult for the user to hear the call arrival sound. In order to avoid this, the call arrival sound is output from the second diaphragm **530** when the mobile terminal device **2300** is closed. Thus, the user can clearly hear the call arrival sound. In a conventional foldable mobile terminal device, it is desired that two electric-mechanical-acoustic-transducers are provided: one for both outputting a sound outside in a closed state, and the other for realizing a dialog in an open state. This enlarges the space required for the electric-mechanical-acoustic-transducers. In the mobile terminal device **2300** according to the present invention, one electric-mechanical-acoustic-transducer is usable both for outputting a sound outside in a closed state and realizing a dialog in an open state. This reduces the space for the electric-mechanical-acoustic-transducer.

[0190] The speaker system **1200** in the third example including the electric-mechanical-acoustic-transducer **322** instead of the electric-mechanical-acoustic-transducer **32** may be used instead of the speaker system **1600**.

(Example 9)

[0191] An electronic device **2400** according to a ninth example of the present invention will be described with reference to Figures **21A** and **21B**. Figure **21A** is a plan view of the electronic device **2400**. Figure **21B** is a cross-sectional view of the electronic device **2400** taken along chain line **K-L** shown in Figure **21A**.

[0192] In this example, the electronic device **2400** is described as a PDA. However, the electronic device **2400** is not limited to a PDA.

[0193] The electronic device **2400** includes a housing **150** and a speaker system **1700**. The speaker system **1700** is a modification example of the speaker system **1200** described in the third example (Figures **7A** and **7B**). The speaker system **1700** includes a display panel **321** and a transparent panel **234** instead of the display panel **21** and the transparent panel **34**. The display panel **321** has substantially the same function as that of the display panel **21**. The transparent panel **234** is a film formed of PET, acrylic resins or other transparent resins. The electronic device **2400** includes a space **337** between the display panel **321** and the transparent panel **234**. The space **337** is preferably a closed space. In the speaker system **1700**, the display panel **321** and transparent panel **234** are supported by the housing **150**. The display panel **321** is supported such that an image displayed in the display panel **321** can be viewed from outside.

[0194] A surface of the transparent panel **234** is coated with a conductive film **160** such that the resistivity of the surface of the transparent panel **234** is uniform. The transparent panel **234** acts as a transparent conductor. Electrodes **156**, **157**, **158** and **159** are provided along the four sides of the surface of the transparent panel **234**. The electronic device **2400** also includes a control section **155** for processing an image signal and an acoustic signal. The display panel **321** is driven by the control section **155** so as to drive operation menu icons **161** or the like. The control section **155** applies a voltage to the electrodes **156**, **157**, **158** and **159**. The transparent panel **234** acts as a touch panel.

[0195] An exemplary operation of the electronic device **2400** will be described. The speaker system **1700** operates in substantially the same manner as the speaker system **1200**.

[0196] The user puts an icon click-dedicated input pen **162** or the user's finger as a contact member into contact with a position of the transparent panel **234** corresponding to one of the operation menu icons **161** and applies a pressure to the position. When the icon click-dedicated input pen **162** or the user's finger contacts the transparent panel **234**, a current flows from the electrodes **156**, **157**, **158** and **159** to the icon click-dedicated input pen **162** owing to the static capacitance of the icon click-dedicated input pen **162** or the user's finger. By the flow of the current through the electrodes **156**, **157**, **158** and **159**, the contact of the icon click-dedicated input pen **162** to the transparent panel **234** is detected. Based on the value of the current flowing through each of the electrodes **156**, **157**, **158** and **159**, the control section **155** calculates the coordinate value of the position of the transparent panel **234** which is in contact with the icon click-dedicated input pen **162** or the user's finger. In accordance with the content of the operation menu icon **161** corresponding to the detected coordinate value, the control section **155** causes the electronic device **2400** to perform a prescribed function (for example, sending or receiving of an electronic mail).

[0197] An operation of a general touch panel is disclosed by Japanese Laid-Open Publication No. 9-265341. According to the present invention, the transparent panel **234** acts as a static capacitance system touch panel. Namely, the transparent panel **234** is used both as a touch panel and a transparent panel for acoustic signal reproduction. The electronic device including the touch panel has a space between the display panel and the touch panel. The sound output from the electric-mechanical-acoustic-transducer is transferred to the space, and thus the sound is output from the touch panel.

[0198] An electronic device, including a panel which is usable both as the touch panel and the transparent panel for acoustic signal reproduction, reproduces a sound from the touch panel. The component for acoustic signal reproduction can be simplified. In such an electronic device, a speaker system according to the present

invention can be easily produced. The touch panel is transparent and transmissive with respect to visible light. Therefore, the touch panel does not shield an image displayed in the display panel.

[0199] In this example, the transparent panel **234** is also used as a static capacitance system touch panel. Alternatively, the transparent panel **234** may also be used as an optical system touch panel. The optical system touch panel includes a plurality of light emitting elements and a plurality of light receiving elements. The optical system touch panel detects that the light emitted by one of light emitting elements is shielded before reaching the corresponding light receiving element, and thus detects the position of the transparent panel **234** which is in contact with the contact member. Still alternatively, the transparent panel **234** may be, for example, an electromagnetic induction type system panel or an ultrasonic system touch panel. The electromagnetic induction system touch panel uses a loop antenna to detect the position of the transparent panel **234** which is in contact with a contact member including a resonating circuit. The ultrasonic system touch panel uses a vibration sensor to detect the position of the transparent panel **234** which is in contact with a contact member including an ultrasonic diaphragm. Regardless of the system, substantially the same effect is provided. In any of these systems, one panel can be used both as a touch panel and a vibration panel. The method for detecting the position in the transparent panel **234** using the touch panel is not limited to the above.

[0200] The speaker system **1300** described in the third example may be used in the speaker system **1700**.

(Example 10)

[0201] An electronic device **2500** according to a tenth example of the present invention will be described with reference to Figures **22A** and **22B**. Figure **22A** is a plan view of the electronic device **2500**. Figure **22B** is a cross-sectional view of the electronic device **2500** taken along chain line **M-N** shown in Figure **22A**.

[0202] In this example, the electronic device **2500** is described as a PDA. However, the electronic device **2500** is not limited to a PDA, but may be an installation type electronic device.

[0203] The electronic device **2500** includes a housing **250** and a speaker system **1800**. The speaker system **1800** is a modification example of the speaker system **1300** described in the third example (Figures **9A** and **9B**). The speaker system **1800** includes a display panel **321**, a transparent panel **324** and a substrate **327** instead of the display panel **21**, the transparent panel **224** and the substrate **227**. The display panel **324** is a film formed of PET, acrylic resins or other transparent resins. The substrate **327** is formed of a transparent material formed of, for example, polycarbonate. In the speaker system **1800**, the display panel **321** and the substrate **327** are supported by the housing **250**. The display pan-

el **321** is supported by the housing **250** such that an image displayed in the display panel **321** can be viewed from outside. The substrate **327** has a sound hole **613**, which is communicated to the opening 36 of the acoustic pipe (not shown in Figure **22A** or **22B**).

[0204] A transparent electrode **114** having an electric resistance is provided on a top surface of the substrate **327**. A transparent electrode **124** having an electric resistance is provided on a bottom surface of the transparent panel **324**. On a top surface of two shorter sides of the spacer **625**, electrodes **131** and **132** are provided for detecting an electric resistance. The electrodes **131** and **132** are in contact with the transparent electrode **124**. On a bottom surface of two longer sides of the spacer **625**, electrodes **133** and **134** are provided for detecting an electric resistance. The electrodes **133** and **134** are in contact with the transparent electrode **114**. The electronic device **2500** includes a space **326** between the transparent electrode **114** provided on the substrate **327** and the transparent electrode **124** provided on the transparent panel **324**. The transparent panel **324** and the substrate **327** are connected to each other via a spacer **625**. The space **326** is preferably a closed space. The electronic device **2500** further includes a control section **255** for processing an image signal and an acoustic signal. The display panel **321** is driven by the control section **255** and displays, for example, operation menu icons **161**. The control section **255** applies a voltage to the electrodes **131**, **132**, **133** and **134**. The transparent panel **324** and the substrate **327** act as a touch panel. The transparent electrode **114** has a rectangular sound hole **623**.

[0205] An exemplary operation of the electronic device **2500** will be described. The speaker system **1800** operates in substantially the same manner as the speaker system **1300** described in the third example.

[0206] The control section **155** applies a voltage to the electrodes **156**, **157**, **158** and **159**. The user puts the icon click-dedicated input pen **162** (Figure **21A**) or the user's finger as a contact member into contact with a position of the transparent panel **324** corresponding to one of the operation menu icons **161** displayed in the display panel **321** and applies a pressure to the position. The application of the pressure causes the transparent electrode **114** and the transparent electrode **124** into contact with each other. Thus, an electric current flows to each of the electrodes **131**, **132**, **133** and **134**, and the contact of the icon click-dedicated input pen **162** to the transparent panel **324** is detected. The control section **255** detects the value of the current flowing through each of the electrodes **131**, **132**, **133** and **134**. Based on the value of the current, the electric resistance between the electrodes **131**, **132**, **133** and **134** is calculated. Based on the calculated electric resistance, the control section **255** calculates the coordinate value of the position at which the transparent electrodes **114** and **124** contact each other. The control section **255** causes the electronic device **2500** to operate with a prescribed

function in accordance with the content of the menu icon **161** corresponding to the detected coordinate value.

[0207] In this example, the transparent panel **324** acts as a resistance film system touch panel. In other words, the transparent panel **324** acts both as a touch panel and as a transparent panel for acoustic signal reproduction. The acoustic pipe is provided in connection with the space **326**, and a sound output from an electric-mechanical-acoustic-transducer is transferred to the space **326**. Thus, the sound from the touch panel can be easily output. In a structure of using a resistance film system touch panel, a space is necessarily and easily provided between the touch panel and the display panel or the substrate.

[0208] An electronic device, including a panel which is usable both as the touch panel and the transparent panel for acoustic signal reproduction, reproduces a sound from the touch panel. The component for acoustic signal reproduction can be simplified. In such an electronic device, a speaker system according to the present invention can be easily produced. The touch panel is transparent and transmissive with respect to visible light. Therefore, the touch panel does not shield an image displayed in the display panel.

[0209] The spacer **625** is provided in order to form the space **326** between the substrate **327** and the transparent panel **324** for transferring a sound. The spacer **625** may be an adhesive or an adhesive film.

[0210] In this example, the transparent panel **324** also acts as a resistance film system touch panel. Alternatively, the transparent panel **324** may also act as, for example, an electrostatic system, an optical system, an electromagnetic system, or an ultrasonic system touch panel. Regardless of the system, substantially the same effect is provided.

[0211] The substrate **327** may be omitted and the transparent electrode **124** may be provided on the display panel **321**. By omitting the substrate **327**, the structure of the electronic device **2500** is further simplified. The speaker system **1200** in the third example may be used instead of the speaker system **1800**.

(Example 11)

[0212] In the electronic device **2400** in the ninth example and the electronic device **2500** in the tenth example, the transparent panels **234** and **324** are provided such that an image displayed in the display panel **321** is viewed through the transparent panels **234** and **324**. A panel for acoustic signal reproduction also acting as a touch panel can operate as a touch panel even though it is not transparent. In this case, the display panel below the panel for acoustic signal reproduction is omitted, but a sound can be output from the panel for acoustic signal reproduction by forming a space below the panel for acoustic signal reproduction for transferring the sound. In an eleventh example of the present invention, an electronic device **2401** including such a non-transparent

panel will be described with reference to Figures 23A and 23B.

[0213] Figure 23A is a plan view of the electronic device 2401, and Figure 23B is a cross-sectional view of the electronic device 2401 taken along chain line K₁-L₂ shown in Figure 23A.

[0214] The electronic device 2401 includes a speaker system 1701 and a housing 650 for supporting the speaker system 1701. The speaker system 1701 includes a panel 634, an electric-mechanical-acoustic-transducer 32, and an acoustic pipe 33. The acoustic pipe 33 acts as an acoustic signal transfer member for transferring a sound output from the electric-mechanical-acoustic-transducer 32 to a space 637 provided between the panel 634 and the housing 650. A peripheral portion of the panel 634 is supported by the housing 650, and the panel 634 is vibrated by the sound transferred from the electric-mechanical-acoustic-transducer 32 to the space 637 via the acoustic pipe 33. The space 637 is preferably a closed space.

[0215] The speaker system 1701 is obtained by eliminating the display panel 321 from the structure of the speaker system 1700 (Figure 21B). The panel 634 is non-transparent. The operation of the panel 634 being vibrated by the sound output from the electric-mechanical-acoustic-transducer 32 and generating a sound is similar to the operation of the panel 234 being vibrated by the sound output from the electric-mechanical-acoustic-transducer 32 and generating a sound in the speaker system 1700.

[0216] The panel 634 has an operation menu 661 on a surface thereof. The operation menu 661 is, for example, printed on the surface of the panel 634. The surface of the panel 634 with the operation menu 661 is coated with a conductive film 660 such that the resistivity of the surface of the transparent panel 634 is uniform. The panel 634 acts as a conductor. Electrodes 656, 657, 658 and 659 are provided along the four sides of the surface of the transparent panel 634. The electronic device 2401 includes a control section 655 for processing an acoustic signal. The electronic device 2401 further includes a control section 655 for processing an acoustic signal. The control section 655 applies a voltage to each of the electrodes 656, 657, 658 and 659. The panel 634 acts as a touch panel like the transparent panel 234 described in the ninth example.

[0217] The user puts an icon click-dedicated input pen 662 or the user's finger as a contact member into contact with a position of the transparent panel 634 corresponding to an item of the operation menu 661 and applies a pressure to the position. The operation for detecting the position of the transparent panel 634 which is in contact with the icon click-dedicated input pen 662 or the user's finger is substantially the same as the operation described in the ninth example. The control section 655 causes the electronic device 2401 to operate with a prescribed function in accordance with the content of the item of the operation menu 661 at the detected position.

[0218] In this example, the panel 634 also acts as a panel for acoustic signal reproduction. An electronic device, including a panel which is usable both as the touch panel and the panel for acoustic signal reproduction, reproduces a sound from the touch panel.

[0219] The speaker system 1701 may further include a substrate so as to provide a space between the substrate and the panel 634. An electronic device 2402 including a speaker system 1702 including a substrate 427 will be described with reference to Figures 24A and 24B.

[0220] Figure 24A is a plan view of the electronic device 2402, and Figure 24B is a cross-sectional view of the electronic device 2402 taken along chain line K₂-L₂ shown in Figure 24A.

[0221] The substrate 427 is provided so as to face the panel 634, and a space 737 is provided between the substrate 427 and the transparent panel 634. The electronic device 2402 includes a housing 750 for supporting the substrate 427. The panel 634 and the substrate 427 are connected to each other via a spacer 725. The space 737 is preferably a closed space. The operation of the electronic device 2402 for generating a sound from the panel 634 and the operation of the panel 634 as a touch panel are substantially the same as those of the electronic device 2401.

[0222] In this example, the panel 634 also acts as an electrostatic capacitance system touch panel. Alternatively, electrodes as described in the tenth example may be provided on the panel 634, the housing 650 and the substrate 427, so that the panel 634 also acts as a resistance film system touch panel. The panel 634 may also act as, for example, an optical system, an electromagnetic system, or an ultrasonic system touch panel. Regardless of the system, substantially the same effect is provided.

(Example 12)

[0223] An electronic device 2600 according to a twelfth example of the present invention will be described with reference to Figures 25 and 26. Figure 25 is an isometric view of the electronic device 2600, and Figure 26 is a cross-sectional view of a speaker system included in the electronic device 2600 taken along chain line O-P shown in Figure 25.

[0224] In this example, the electronic device 2600 is described as a notebook computer, which is a mobile terminal device. The electronic device 2600 is not limited to a notebook computer. The electronic device 2600 may be, for example, an installation type electronic device.

[0225] The electronic device 2600 includes a housing 170 for accommodating, for example, a CPU and memories (not shown), and a speaker system 1900.

[0226] The speaker system 1900 includes a display panel 421, a transparent panel 172 provided such that an image displayed in the display panel 421 is viewed

through the display panel **421**, an electric-mechanical-acoustic-transducer **422** having a diaphragm **45** (Figure **26**) for vibrating the diaphragm **45** in accordance with an electric signal so as to output a sound, and a housing **173** for supporting the transparent panel **172** and the display panel **421**.

[0227] The speaker system **1900** has a space **189** between the display panel **421** and the transparent panel **172**. The space **189** is preferably a closed space. The housing **173** has a sound hole **288**. The housing **173** acts as an acoustic signal transfer member for transferring a sound output from the electric-mechanical-acoustic-transducer **422** to the space **189**. The transparent panel **172** is vibrated by a sound transferred from the electric-mechanical-acoustic-transducer **422** to the space **189** via the sound hole **288**. The transparent panel **172** has an area larger than the area of the diaphragm **45**. The display panel **421** may be a liquid crystal display. The transparent panel **172** is formed of PET, glass, an acrylic resin or other materials transmissive with respect to visible light. The electric-mechanical-acoustic-transducer **422** is rectangular.

[0228] The electric-mechanical-acoustic-transducer **422** is a modification example of the electric-mechanical-acoustic-transducer **22** shown in Figure **2**. The electric-mechanical-acoustic-transducer **422** includes a housing **186**. In this example, the diaphragm **45** is rectangular. In Figure **26**, the shorter side of the diaphragm **45** is shown. The housing **186** covers a top surface and side surfaces of the diaphragm **45** and forms an empty space **187**. The housing **186** has a slit opening **188**. The opening **188** is communicated with the sound hole **288** of the housing **173**.

[0229] The speaker system **1900** operates in substantially the same manner as the speaker system **1000** described in the first example including the electric-mechanical-acoustic-transducer **22**. Specifically, a sound which is output from the diaphragm **45** of the electric-mechanical-acoustic-transducer **422** is transferred to the space **189** via the empty space **187**, the opening **188** and the sound hole **288**. The transparent panel **172** is vibrated by the pressure of the sound transferred to the space **189** so as to generate a sound. The speaker system **1900** may further include an electric-mechanical-acoustic-transducer **522**. The electric-mechanical-acoustic-transducer **522** includes substantially the same components as those of the electric-mechanical-acoustic-transducer **422**. When including the electric-mechanical-acoustic-transducer **522**, the speaker system **1900** operates in substantially the same manner as the speaker system **1400** described in the fourth example. The speaker system **1900** can provide a stereo reproduction.

[0230] The opening **188** of the housing **186** extends in a direction vertical to a direction in which the diaphragm **45** vibrates. The sound hole **288** of the housing **173**, which is in communication with the opening **188**, is formed in a direction parallel to a direction in which dis-

play panel **421** extends. Owing to such a structure, the electric-mechanical-acoustic-transducer **422** can be provided on the same plane as, and adjacent to, the display panel **421**, which can provide the speaker system **1900** with a decreased thickness. The sound output from the diaphragm **45** of the electric-mechanical-acoustic-transducer **422** is transferred parallel to the display panel **421**. The electric-mechanical-acoustic-transducer **522** can also be provided in the same plane as, and adjacent to, the display panel **421**. Therefore, when including the electric-mechanical-acoustic-transducer **522**, the speaker system **1900** can be also thin.

[0231] The transparent panel **172** is provided such that an image displayed in the display panel **421** is viewed through the display panel **421**. Therefore, in the personal computer **2600**, the position at which an image is displayed to the user is the same as the position from which a sound is output to the user.

[0232] A speaker system according to the present invention is easily applicable to an electronic device including a display panel, for example, a TV, a game machine, or a car navigation system. The transparent panel may act only as a diaphragm for outputting a sound, or may act both as a diaphragm and a touch panel.

[0233] In the case where the electric-mechanical-acoustic-transducer has a function of a mechanical vibration function as well as an acoustic signal reproduction function, the two functions can be separately used for specific purposes.

[0234] The present invention provides a speaker system including a transparent panel provided such that an image displayed in a display panel is viewed through the transparent panel. The transparent panel can be vibrated. Owing to such a structure, the position at which the image is displayed to the user can be the same as the position from which a sound is output to the user.

[0235] According to the present invention, a sound output from a diaphragm having a smaller area is transferred to a space, and a transparent panel having a larger area is vibrated by the sound transferred to the space. Owing to such a structure, even when the transparent panel is relatively heavy, the transparent panel can be vibrated and a sound having a sufficient volume can be output by a small force which is sufficient to vibrate a diaphragm.

[0236] According to the present invention, a substrate is provided between the display panel and the transparent panel. Since the substrate protects the display panel against external impacts, the transparent panel can be formed to be thinner, which improves the acoustic characteristics of the transparent panel.

[0237] According to the present invention, an acoustic pipe is provided as an acoustic signal transfer member for transferring a sound output from an electric-mechanical-acoustic-transducer to the space. Owing to such a structure, the freedom of locating the speaker system in an electronic device or a mobile terminal device including the speaker is increased. Since it is not necessary

that the electric-mechanical-acoustic-transducer be provided adjacent to the display panel, the space in which the display panel can be provided can be enlarged, which increases the size of the display panel.

[0238] In the case where a speaker system according to the present invention is mounted on a mobile terminal device (for example, a cellular phone), the transparent panel can operate as a diaphragm of a receiver for reproducing a received sound. Since the received sound is reproduced from the entire surface of the transparent panel, the user can hear the received sound wherever the user's ear may be located on the transparent panel having a relatively large area. This eliminates the necessity of putting the position of the user's ear at one particular position of the transparent panel. The user's ear is never deviated from the sound source. Such a mobile terminal device allows especially an aged user to easily hear the received sound. When the level of the electric signal applied to the speaker system is raised, the speaker system acts as a loudspeaker for outputting a sound having a large volume even when separated from the main body of the mobile terminal device. In this case, the user can use the mobile terminal device as a video phone, by which the user can perform a dialog with a person on the other end while viewing an image on a screen. Since the position at which the image is displayed to the user is the same as the position from which the sound is output to the user, a realistic sound reproduction is provided. Such a mobile terminal device is optimum for simultaneously reproducing a sound and an image.

[0239] In the case where the speaker system according to the present invention includes a plurality of electric-mechanical-acoustic-transducers, multiple channel reproduction, for example, a stereo reproduction, is realized.

[0240] In the case where the electric-mechanical-acoustic-transducer has a mechanical vibration function as well as an acoustic signal reproduction function, the speaker system can simultaneously perform the two functions of acoustic signal reproduction and mechanical vibration.

[0241] In an electric device including a touch panel, the touch panel can also be used as a transparent panel of the speaker system according to the present invention. In this case, the speaker system according to the present invention can be easily produced.

[0242] Various other modifications will be apparent to and can be readily made by those skilled in the art without departing from the scope and spirit of this invention. Accordingly, it is not intended that the scope of the claims appended hereto be limited to the description as set forth herein, but rather that the claims be broadly construed.

Claims

1. A speaker system, comprising:

a display panel for displaying an image;
a transparent panel provided such that the image displayed in the display panel is viewed through the transparent panel;
an electric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and
an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the display panel and the transparent panel,

wherein the transparent panel is allowed to be vibrated by the sound transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member.

2. A speaker system according to claim 1, wherein:

the acoustic signal transfer member is a housing for supporting the transparent panel, the housing has a sound hole, and the sound is transferred to the space via the sound hole.

3. A speaker system according to claim 1, further comprising an elastic member for supporting a peripheral portion of the transparent panel.

4. A speaker system according to claim 1, wherein the acoustic signal transfer member is an acoustic pipe.

5. A speaker system according to claim 1, wherein a thickness of a peripheral portion of the transparent panel is smaller than a thickness of a central portion of the transparent panel.

6. A speaker system according to claim 1, wherein the transparent panel is a film

7. A speaker system according to claim 1, wherein the electric-mechanical-acoustic-transducer includes a mechanical vibration section for generating a mechanical vibration.

8. A speaker system according to claim 1, comprising:

at least one more electric-mechanical-acoustic-transducer; and
at least one more acoustic signal transfer member,

wherein:

the electric-mechanical-acoustic-transducers each include a diaphragm and each output a sound by vibrating the diaphragm in accordance with an electric signal, the acoustic signal transfer members each transfer the sound output from the respective electric-mechanical-acoustic-transducer to the space, and the acoustic signal transfer members are connected to the space at different positions.

9. A speaker system according to claim 1, wherein:

the acoustic signal transfer member has a sound hole for transferring the sound, and the sound hole extends in a direction parallel to a direction in which the display panel extends.

10. A speaker system according to claim 1, wherein:

the electric-mechanical-acoustic-transducer includes a housing for surrounding the diaphragm, the housing has an opening extending in a direction vertical to a direction in which the diaphragm vibrates, and the opening is in connection with the acoustic signal transfer member.

11. A mobile terminal device, comprising:

a speaker system; and
a housing for supporting the speaker system,

wherein the speaker system includes a display panel for displaying an image; a transparent panel provided such that the image displayed in the display panel is viewed through the transparent panel; an electric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the display panel and the transparent panel, wherein the transparent panel is allowed to be vibrated by the sound transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member,

the mobile terminal device further comprising:

an antenna for receiving a wireless signal; and
a signal output section for outputting an electric signal to the electric-mechanical-acoustic-transducer based on the wireless signal received by the antenna,

wherein the electric signal represents at least one of a received sound, a call arrival sound, music and voice.

12. A mobile terminal device according to claim 11, wherein when the electric signal represents the received sound, the transparent panel acts as a receiver.

13. A mobile terminal device according to claim 11, wherein when the electric signal represents one of the call arrival sound, the music and the voice, the transparent panel acts as a loudspeaker.

14. A mobile terminal device according to claim 11, wherein:

the electric-mechanical-acoustic-transducer includes one more diaphragm,

the housing has a sound hole,

one of the diaphragms is provided so as to face the acoustic signal transfer member, and

the other diaphragm is provided so as to face the sound hole.

15. An electronic device, comprising:

a speaker system; and
a housing for supporting the speaker system,

wherein the speaker system includes a display panel for displaying an image; a transparent panel provided such that the image displayed in the display panel is viewed through the transparent panel; an electric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the display panel and the transparent panel, wherein the transparent panel is allowed to be vibrated by the sound transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member.

16. An electronic device according to claim 15, further comprising a control section for controlling an operation of the electronic device, wherein:

the transparent panel also acts as a touch panel for detecting a contact of a contact member with a position of the transparent panel corresponding to an operation menu icon displayed in the

- display panel, and
the control section causes the electronic device
to operate in accordance with the operation
menu icon corresponding to the position of the
transparent panel which is in contact with the
contact member.
17. An electronic device according to claim 16, wherein
the touch panel is one of an electrostatic system
touch panel, an optical system touch panel, an elec-
tromagnetic system touch panel, and an ultrasonic
system touch panel.
18. A speaker system, comprising:
a display panel for displaying an image;
a transparent panel provided such that the im-
age displayed in the display panel is viewed
through the transparent panel;
a substrate provided between the display panel
and the transparent panel such that the image
is viewed through the substrate;
an electric-mechanical-acoustic-transducer
having a diaphragm for outputting a sound by
vibrating the diaphragm in accordance with an
electric signal; and
an acoustic signal transfer member for trans-
ferring the sound output from the electric-me-
chanical-acoustic-transducer to a space pro-
vided between the transparent panel and the
substrate,
wherein the transparent panel is allowed to be
vibrated by the sound transferred to the space from
the electric-mechanical-acoustic-transducer via the
acoustic signal transfer member.
19. A speaker system according to claim 18, wherein:
the substrate has a sound hole, and
the substrate acts as the acoustic signal trans-
fer member.
20. A speaker system according to claim 18, wherein
the space is provided among a spacer, for connect-
ing a peripheral portion of the transparent panel and
a peripheral portion of the substrate, the transpar-
ent panel and the substrate.
21. A speaker system according to claim 18, wherein
the transparent panel is a film.
22. A speaker system according to claim 18, wherein
the acoustic signal transfer member is an acoustic
pipe.
23. A speaker system according to claim 18, compris-
ing:
- at least one more electric-mechanical-acous-
tic-transducer; and
at least one more acoustic signal transfer mem-
ber,
wherein:
the electric-mechanical-acoustic-transducers
each include a diaphragm and each output a
sound by vibrating the diaphragm in accord-
ance with an electric signal,
the acoustic signal transfer members each
transfer the sound output from the respective
electric-mechanical-acoustic-transducer to the
space, and
the acoustic signal transfer members are con-
nected to the space at different positions.
24. A mobile terminal device, comprising:
a speaker system; and
a housing for supporting the speaker system,
wherein the speaker system includes a dis-
play panel for displaying an image; a transparent
panel provided such that the image displayed in the
display panel is viewed through the transparent
panel; a substrate provided between the display
panel and the transparent panel such that the image
is viewed through the substrate; an electric-me-
chanical-acoustic-transducer having a diaphragm
for outputting a sound by vibrating the diaphragm in
accordance with an electric signal; and an acoustic
signal transfer member for transferring the sound
output from the electric-mechanical-acoustic-trans-
ducer to a space provided between the transparent
panel and the substrate, wherein the transparent
panel is allowed to be vibrated by the sound trans-
ferred to the space from the electric-mechanical-
acoustic-transducer via the acoustic signal transfer
member, the mobile terminal device further com-
prising:
an antenna for receiving a wireless signal; and
a signal output section for outputting an electric
signal to the electric-mechanical-acoustic-
transducer based on the wireless signal re-
ceived by the antenna,
wherein the electric signal represents at least
one of a received sound, a call arrival sound, music
and voice.
25. A mobile terminal device according to claim 24,
wherein when the electric signal represents the re-
ceived sound, the transparent panel acts as a re-
ceiver.

26. A mobile terminal device according to claim 24, wherein when the electric signal represents one of the call arrival sound, the music and the voice, the transparent panel acts as a loudspeaker.

5

27. A mobile terminal device according to claim 24, wherein:

the electric-mechanical-acoustic-transducer has one more diaphragm, the housing has a sound hole, one of the diaphragms is provided so as to face the acoustic signal transfer member, and the other diaphragm is provided so as to face the sound hole.

10

15

28. An electronic device, comprising:

a speaker system; and
a housing for supporting the speaker system,

20

wherein the speaker system includes a display panel for displaying an image; a transparent panel provided such that the image displayed in the display panel is viewed through the transparent panel; a substrate provided between the display panel and the transparent panel such that the image is viewed through the substrate; an electric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the transparent panel and the substrate, wherein the transparent panel is allowed to be vibrated by the sound transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member.

25

30

35

40

29. An electronic device according to claim 28, further comprising a control section for controlling an operation of the electronic device, wherein:

45

the transparent panel also acts as a touch panel for detecting a contact of a contact member with a position of the transparent panel corresponding to an operation menu icon displayed in the display panel, and the control section causes the electronic device to operate in accordance with the operation menu icon corresponding to the position of the transparent panel which is in contact with the contact member.

50

55

30. An electronic device according to claim 29, further comprising:

a first transparent electrode having an electric resistance and provided on a surface of the transparent panel facing the substrate; and a second transparent electrode having an electric resistance and provided on a surface of the substrate facing the transparent panel.

31. An electronic device, comprising:

a speaker system; and
a housing for supporting the speaker system,

wherein:

the speaker system includes a panel; an electric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the panel and the housing, and the panel is allowed to be vibrated by the sound transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member, the electronic device further includes a control section for controlling an operation of the electronic device, the panel also acts as a touch panel for detecting a contact of a contact member with a position of the panel corresponding to an item of an operation menu provided on the panel, and the control section causes the electronic device to operate in accordance with the item of the operation menu corresponding to the position of the panel which is in contact with the contact member.

32. An electronic device, comprising:

a speaker system; and
a housing for supporting the speaker system,

wherein:

the speaker system includes a panel; a substrate provided so as to face the panel; an electric-mechanical-acoustic-transducer having a diaphragm for outputting a sound by vibrating the diaphragm in accordance with an electric signal; and an acoustic signal transfer member for transferring the sound output from the electric-mechanical-acoustic-transducer to a space provided between the panel and the substrate, and the panel is allowed to be vibrated by the sound

transferred to the space from the electric-mechanical-acoustic-transducer via the acoustic signal transfer member,
 the electronic device further includes a control section for controlling an operation of the electronic device, 5
 the panel also acts as a touch panel for detecting a contact of a contact member with a position of the panel corresponding to an item of an operation menu provided on the panel, and 10
 the control section causes the electronic device to operate in accordance with the item of the operation menu corresponding to the position of the panel which is in contact with the contact member. 15

33. A speaker system according to claim 8, wherein:

the electric signal represents at least one of a received sound, a call arrival sound, and audio information for a plurality of channels, 20
 when the electric signal represents at least one of the received sound and the call arrival sound, the electric signal is input to the electric-mechanical-acoustic-transducers, and 25
 when the electric signal represents the audio information for the plurality of channels, an electric signal representing audio information for each of the plurality of channels is input to the respective electric-mechanical-acoustic-transducer. 30

34. A mobile terminal device according to claim 11, wherein:

the speaker system includes: 35

at least one more electric-mechanical-acoustic-transducer, and
 at least one more acoustic signal transfer member, and 40
 the electric-mechanical-acoustic-transducers each include a diaphragm and each output a sound by vibrating the diaphragm in accordance with an electric signal, 45
 the acoustic signal transfer members each transfer the sound output from the respective electric-mechanical-acoustic-transducer to the space,
 the acoustic signal transfer members are connected to the space at different positions, 50
 when the electric signal represents at least one of the received sound and the call arrival sound, the electric signal is input to the electric-mechanical-acoustic-transducers, and 55
 when the electric signal represents the au-

dio information for the plurality of channels, an electric signal representing audio information for each of the plurality of channels is input to the respective electric-mechanical-acoustic-transducer.

35. A speaker system according to claim 23, wherein:

the electric signal represents at least one of a received sound, a call arrival sound, and audio information for a plurality of channels,
 when the electric signal represents at least one of the received sound and the call arrival sound, the electric signal is input to the electric-mechanical-acoustic-transducers, and
 when the electric signal represents the audio information for the plurality of channels, an electric signal representing audio information for each of the plurality of channels is input to a respective one of the electric-mechanical-acoustic-transducers.

FIG. 1A




FIG. 1B




FIG. 2





FIG. 3

FIG. 4




FIG. 5





FIG. 6

FIG. 7A




FIG. 7B




FIG. 8




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19A




FIG. 19B




FIG. 19C




FIG. 20




FIG. 21A




FIG. 21B




FIG. 22A




FIG. 22B




FIG. 23A




FIG. 23B




FIG. 24A




FIG. 24B




FIG. 25




FIG. 26




FIG. 27

